Our commitment. Your advantage.

Search

Products


Documentation

Resources

My Account

Customer Support

640426-4 Product Details



640426-4

TE Internal Number: 640426-4



MTA, CST-100 II, MT-6 and SL Connectors and Headers

Not EU RoHS or ELV Compliant (Find RoHS Compliant Alternates)

Product Highlights:

- Connector
- 4 Positions
- Connector Type = Receptacle Connector Style = Closed End
- MTA-156 Product Line

View all Features

Add to My Part List

Request Sample

Find Similar Products

Buy Product

Ouick Links

- Check Pricing & Availability
- Search for Tooling
- View Mating Products (42) Product Feature Selector
- Contact Us About This Product

View 3D PDF **Documentation & Additional Information**

Product Drawings:

• MTA 156 CONNECTOR ASSEMBLY, 18 AWG, STANDARD (PDF, English)

Catalog Pages/Data Sheets:

MTA, CST-100 II, SL-156 and AMP Economy Power (EP) C... (PDF, English)

Product Specifications:

Connector, MTA 156, Wire-To-Wire System (PDF, English)

Application Specifications:

• MTA 156 Connector (PDF, English)

Instruction Sheets:

MTA Terminating Head (PDF, English)

CAD Files: (CAD Format & Compression Information) ■ 2D Drawing (DXF, Version M)

- <u>3D Model</u> (IGES, Version M)
- 3D Model (STEP, Version M)

Additional Information:

- **Product Information**
- · Product Line Information

Related Products:

- Tooling
- Mating Products (42)

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Connector • Number of Positions = 4
- Connector Type = Receptacle • <u>Connector Style</u> = Closed End
- Product Line = MTA-156
- Wire Termination Type = IDC Standard
- Wire Size (mm² [AWG]) = 0.8-0.9² [18]
- <u>Mating Polarization</u> = Without
- Mating Connector Lock = With
- <u>Four Points of Contact</u> = Without
- <u>Shrouded</u> = No
- Mounting Ears = Without
- Mating Connector Lock Type = Locking Ramp

Mechanical Attachment:

Panel Attachment = Without

Electrical Characteristics:

- Current Rating (Amps.) = 7
- Voltage Rating (VAC) = 600

Termination Related Features:

• Solder Tail Contact Plating = Tin-Lead

Body Related Features:

- Narrow = No
- Post Number(s) Omitted = None
- Cable Exit Angle = 90°

Contact Related Features:

- Contact Centerline Spacing (mm [in]) = 3.96 [0.156]
- Contact Plating, Mating Area, Material = Tin-Lead
- Contact Base Material = Copper Alloy

Housing Related Features:

- Housing Color = Orange
- Housing Flammability Rating = UL 94V-2
- Housing Material = Nylon

Industry Standards:

- RoHS/ELV Compliance = Not ELV/RoHS compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process

Conditions for Usage:

• <u>Terminate To</u> = Wire

Operation/Application:

• Application = Wire-to-Board

• Brand = AMP