

PROHEAT® VARITEMP® HEAT GUN & KIT

MASTER
APPLIANCE

Quick Jump: [Proheat Varitemp Heat Gun and Kit](#)

Compact, lightweight, easy-to-use variable temperature heat gun and kit

- Ergonomic design for superb balance and grip
- Variable temperature with patented electronic temperature control system
- Pre-select and maintain any temperature from 130° - 1000° F / 50° - 540°C
- Powerful airflow at 4000 FPM and 16 CFM
- Heavy-duty Lexan® plastic housing with built-in stand for hands-free use
- Protective hand/switch guard and convenient hanging loop
- Kit includes Proheat Varitemp Heat Gun, attachments 35016, 35017, 35292, 35293, 35294, and 35351 storage/carrying case
- Accessories also available separately
- Use to desolder, heat temperature sensitive materials, shrink tubing, terminate specialty connectors and more



ORDERING INFORMATION

MODEL NO.	DESCRIPTION	
PH-1200	Proheat Varitemp Heat Gun, 130°F (50°C) to 1000°F (540°C), 120V, 60 Hz, 11A, 1300W Max	UL US
PH-1200K	Proheat Varitemp Heat Gun Kit includes PH-1200 Varitemp Heat Gun, 3" spreader attachment, 1-1/3" shrink tubing attachment, 1/2" specialty connector, 9/16" reducer, and 5/16" reducer packed in a rugged storage/carrying case	UL US
PH-2200	Proheat Varitemp Heat Gun, 130°F (50°C) to 1000°F (540°C), 230V*, 50/60 Hz, 6.2A, 1426W Max	CE
PH-2200K	Proheat Varitemp Heat Gun Kit includes PH-2200 Varitemp Heat Gun, 3" spreader attachment, 1-1/3" shrink tubing attachment, 1/2" specialty connector, 9/16" reducer, and 5/16" reducer packed in a rugged storage/carrying case	CE

*220-240 volts

*** For Master's New Product Catalog featuring Proheat Heat Guns, please [click here](#).**

*** For Master's New European Product Catalog featuring Proheat Heat Guns, please [click here](#).**



OPTIONAL ACCESSORIES

MODEL NO.	DESCRIPTION
35016	Spreader attachment, 3" - spread air over large area
35017	Heat shrink attachment, 1-1/3" - shrink tubing
35292	Specialty connector attachment, 1/2" - terminate tubing and specialty connectors
35293	Reducer attachment, 9/16" - direct hot air source for desoldering and welding PVC
35294	Pinpoint reducer attachment, 5/16" - pinpoint hot air source for desoldering and welding PVC
35026	Nozzle shield - prevent nozzle contact
35216	Bench stand - position heat gun for various applications
35309	Attachment kit - includes 36017, 35016, 35292, 35293, 35294
35351	Storage/carrying case, 16.25" L x 3.0" W x 11.5" H

SPECIFICATIONS

<ul style="list-style-type: none"> ■ Avg. Temp. 130° F to 1000° F 50°C to 540° C ■ Avg. Air Volume: 16 CFM/453 l/min ■ Avg. Air Velocity: 4000 FPM/1219m/min ■ Motor: Permanent Magnet ■ Dimensions: 8.2" L x 3.0" W x 7.3" H 	<ul style="list-style-type: none"> ■ Nozzle Opening: 1.3" Dia. O.D. ■ Nozzle Opening: 1.3" Dia. O.D. ■ Cordset: 6 ft., 3-wire grounded ■ Net Weight - Single Unit: 1.6 lbs., Kit: 4.5 lbs. ■ Shipping Weight - Single Unit: 2 lbs., Kit: 7 lbs.
--	--

[View Proheat Varitemp Heat Shrink System](#)

[View Replacement Parts List](#)

Users should independently evaluate the suitability of the product for their application.

[HOME](#) [BACK TO PRODUCT LISTING](#)