



Technical Characteristics

| | |
|-----------------------------|---|
| Operating Torque/Force | 3 Inch-Pounds |
| Actuator | Lever Arm (ordered separately) |
| Actuation | CW Trip - CCW Reset |
| Actuator Action | Maintained |
| Total Travel | 90 Degrees |
| Body Material | Zinc Alloy |
| Approvals | UL Listed File Number E42259 CCN NKCR - CSA Certified File Number LR25490 Class 3211-03 - CE Marked |
| Pre-Travel | 45 Degrees |
| Body Type | Standard Plug-In |
| Catalog Reference Number | 9006CT0101 |
| Connection Type | Conduit Entrance (0.5 Inch NPT) |
| Wire Size | #12 to #22 AWG |
| Contact Configuration | 1 N.O./1 N.C. |
| Contact Rating | NEMA A600/Q600 |
| Contact Material | Silver Alloy |
| Contact Operation | Snap Action |
| Maximum Voltage Rating | 600V |
| Ampere Rating | 10A |
| Contact Form | Form Z - SPDT-DB |
| Terminal Type | Screw Clamp |
| Enclosure Rating | NEMA 1/2/4/6/6P/12/13 |
| Head Type | Rotary |
| Mounting Type | Front/Rear |
| Pilot Light | None |
| Type of Duty | Heavy Duty |
| Operating Temperature Range | -20 to 185 Degrees F |
| Type | C |

Shipping and Ordering

| | |
|-------------------|--|
| Category | 21499 - Limit Switches, Heavy Duty, Type C |
| Discount Schedule | CP1 |
| Article Number | 785901783893 |

Generated: 05/28/2009 10:29:45

| | |
|-------------------|---|
| Package Quantity | 10 |
| Weight | 1.23 lbs. |
| Availability Code | Stock Item: This item is normally stocked in our distribution facility. |
| Returnability | Y |

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.