

PROHEAT[®] LCD **Heat Gun**



Compact
Light Weight
Easy-to-Use

Professional
Quality Heat Guns

*PH-1400/PH-2400
Heat Gun*

- Rugged, ergonomic, LCD heat gun with digital display of temperature and air flow. Adjustable heat in 10° increments from 130°F to 1000°F (50°C to 540°C), and adjustable air flow from 6 to 15 CFM (113-453 l/min) provides fast, reliable, flameless heat.
- Easy dial-in settings with powerful heat and air flow to get the job done fast. Electronic temperature control system maintains constant temperature when varying air flow or using attachments.
- Protective electronic closed-loop temperature control system and industrial quality construction keep your Proheat[®] Heat Gun working year after year in factories, laboratories, workshops and jobsites.
- A broad range of optional attachments make Proheat Heat Guns ideal for a wide variety of applications including heating, drying, shrinking, soldering, desoldering and welding.

PROHEAT[®] LCD

Heat Gun

- Compact, light weight, easy-to-use
- The convenience of analog, the precision of digital
- Safety & productivity features at no extra cost
- LCD with digital display of temperature and air flow settings
- Dial-in temperatures in 10° increments from 130°F to 1000°F (50°C to 540°C) displayed in degrees Fahrenheit or Celsius
- Adjustable air flow from 6 to 15 CFM (113 - 453 l/min.)
- Special electronic closed-loop temperature control system maintains constant temperature when varying air flow or using specialty attachments
- Base provides built-in stand for hands-free use
- Balanced ergonomic design and grip prevents operator fatigue
- Power-Interrupt Reset for added safety, prevents heat gun from causing damage when power returns, if left in "On" position during power failure
- Temperature and Air Flow Lock-in feature provides added control, especially for manufacturing supervisors looking for consistent application of heat
- Made in the USA. 12 month warranty
- UL and CUL Listed, CE Certified.
- Use to accurately heat or dry temperature sensitive materials, shrink tubing, packaging, specialty connectors, solder and desolder, bend plastics, cure adhesives, defrost frozen pipes and more
- Multiple attachments & bench stand available

ORDERING INFORMATION

Model No. Description

PH-1400	Proheat LCD Heat Gun
PH-1400-1	Proheat LCD Heat Shrink System includes heat gun, bench stand and specialty connector attachment
PH-1400K	Proheat LCD Heat Gun Kit includes heat gun, 5 attachments and storage case
PH-2400	Proheat LCD Heat Gun
PH-2400-1	Proheat LCD Heat Shrink System includes heat gun, bench stand and specialty connector attachment
PH-2400K	Proheat LCD Heat Gun Kit includes heat gun, 5 attachments and storage case

TECHNICAL SPECIFICATIONS

PH-1400, PH-1400-1, PH-1400K

Voltage:	120V, 60Hz, 11A
Output:	1410W maximum
Temperature:	Variable 130°F - 1000°F (50°C - 540°C)
Air Flow Volume:	6 - 15 CFM (113 - 453 l/min)
Air Flow Velocity:	947 - 3584 FPM (289 - 1219 m/min)
Agency Approvals:	UL, CUL

PH-2400, PH-2400-1, PH-2400K

Voltage:	230V, 50/60Hz, 5.8A
Output:	1410W maximum
Temperature:	Variable 130°F - 1000°F (50°C - 540°C)
Air Flow Volume:	6 - 15 CFM (113 - 453 l/min)
Air Flow Velocity:	947 - 3584 FPM (289 - 1219 m/min)
Agency Approvals:	CE

PH-1400 & PH-2400

Nozzle opening:	.87" diameter
Net Weight:	26 oz (737 g)
Cordset:	6 ft, 3-wire grounded
Motor:	Permanent magnet
Dimensions:	8.2"L x 3.0"W x 7.3"H

Protected by Patent No's. 334.876

As with all electrical equipment and tools, for your safety, read the instruction manual before using.

All information including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of this product for their application. The only obligations of Master Appliance are those in the Standard Terms and Conditions of Sale for this product. In no case will Master Appliance be liable for any incidental indirect, or consequential damages arising from the sale, resale, use or misuse of this product.



Kit includes Proheat LCD Heat Gun, 3-1/2" (89mm) spreader, 1-3/8" (35mm) heat shrink, 1/2" (13mm) specialty connector, 9/16" & 5/16" (8mm & 14mm) reducer attachments with durable storage/carrying case

see website for full line of accessories and attachments

USA
MADE IN

MASTER[®]
APPLIANCE
Designers and Manufacturers of Heat Tools for Industry

FOR MASTER PRODUCTS CONTACT:

Master Appliance Corp.
Racine, WI 53403 USA
800-558-9413 • 262-633-7791
sales@masterappliance.com

www.masterappliance.com