



E-Z-Code[•]

T&B Catalog Number: UPC Number: Description:	EZ-WHS34 78621094847 EZL Wire Marker Label for Wire Range 2- 4, Heat-Shrink White Polyolefin, 3/4 inch, 5 feet length
Status:	Active

Imagos			
	on/bo14_on1		
Image_1_s7	ezyhs14_ez1		
Features			
	Perfect for wire and cable. Print heat-shrink sleeves		
	on the spot.		
	Clear, non smudging lettering. Chemical/solvent		
	resistant. Available in yellow, white, and metallic		
	markers.		
	Flame retardant Polyolefin material, 3:1 shrink ratio.		
	Easy to peel, split-back design.		
General			
Style	Labels		
Color	White		
Wire Range	2-4		
Dimension Information			
Length (feet)	5		
Width (inches)	3/4		
Packaging			
T&B Inner Pack	1		
Package in Units	5		
T&B Sold in UOM	Each		
T&B Weight Per UOM	12 lbs. per 100		
Application Support			
Overview	Available on Website		
Notes			
	Order in multiples of 5 cassettes.		
	Labels fit EZL-100 only.		
Certifications	• •		
RoHS Compliance	Yes		

E-Z-Code°

EZL-75 Thermal Label Printer and EZL Printer Labels

Quick and cost-effective labeling solution!

EZL-75 Thermal Label Printer

If your labeling needs don't quite justify all the high-end features of T&B's EZL-100, now there's a lower cost solution for simple labeling. The EZL-75 thermal label printer is just as easy to use as the EZL-100. Simply type and print. Or don't even bother typing. Instead, use hot keys to choose among the EZL-75's built-in library of symbols and more than 150 commonly used words for security, location and voice/data/video labeling.



- Hot keys provide one-touch flagging for wires and cables and fixed-length labels for faceplates and security panels
- Incremental alpha and numeric printing makes printing distribution panel labels fast and simple
- 13-character backlit display enhances readability
- · Multiple line printing supports up to 2 lines per label
- · Durable bumper safeguards against damage in the tool box
- Uses the same label cassettes (up to ½" width) as EZL-100
 - Specifications
- Dimensions: 4.5" (114mm) W x 7.5" (191mm) H x 2.1" (53mm) D
- Power: 9V DC, using 6 "VA" (not included/batteries or AC adapter
- Weight: 0.8 lbs. (363 grams)

CAT. NO.	DESCRIPTION
EZL-75	Printer (includes (1) ½" white nylon quick-lead cassette tape, quick start card, and user manual, AC power adapter not included
EZL-ADP	Adapter for EZ75 Printer 91(1.5A

Surface Applications		Vinyl and Flex Nylon	Perm. Polyester	Heat Shrink
Wire	9	•		•
Cable	-0-	•		•
Curred	\sim	•		
Smooth		•	•	
Flat		•	•	
Textured	\sim	•	•	
Highly Textured	~~~~	•		
Length	H	11.5	18.0'	5.0*
Width	I	3°, 3° 3°	37, 57 37	57, 57 57, 57

High-performance labels that last!

Wire Marker Labels for EZL Printers

- · Perfect for wire and cable
- Print heat-shrink sleeves on the spot!
- Clear, non-smudging lettering
- Chemical/solvent resistant
- Available in yellow, white, and metallic markers
- Flame retardant, Polyolefin material, 3:1 shrink ratio
- Easy-to-peel, split-back design



Easy barcode printing/

CAT NO.	LABEL SIZE (IN.)	RECOMMENDED WIRE SIZE (AWG)	LENGTH
Clear Polyester			
EZ-CP12	X*	Flat Applications Only	18'
EZ-CP34	S*	Flat Applications Only	18'
Red Vinyl			
EZ-RV34	¥"	Any	18'
White Permanent Polyester			
EZ-WP38	8"	Flat Applications Only	18'
EZ-WP12	X*	Flat Applications Only	18'
EZ-WP34	¥.	Flat Applications Only	18'
Metallic Permanent Polyester			
EZ-MIP38	¥"	Flat Applications Only	18'
EZ-MP12	X*	Flat Applications Only	18'
EZ-MP34*	¥"	Flat Applications Only	18'
White Flexible Nylon			
EZ-WN12	X*	Any	12.5
EZ-WW34*	3°	Any	12.5
Yellow Flexible Nylon			
EZ-YN12	M.	Any	12.5
EZ-YN34	3f.	Any	12.57
Heat-Shrink White Polyoletin La	ibels		
EZ-WHS14	X*	10 - 16	5'
EZ-WHS38	3r	6-14	5'
EZ-WHS12	Х.	4-6	5'
EZ-WHS34	3*	2-4	5'
Heat-Shrink Yellow Polyolefin L	abels		
EZ-YHS14	Х.	10-16	5'
EZ-YHS38	35	6-14	5'
EZ-YHS12	Х.	4-6	5'
EZ-YHS34	3"	2-4	5'
Order in multiples of 5 cassettes. * Lebels IR EZL_1700 celu			

* Labola 計 EZ2-100 ank

VOr ERATE