



Technical Characteristics

| | |
|-----------------------------|---|
| Control Source | Separate Control Circuit |
| Catalog Reference Number | 8502CT9701 |
| Depth | 4.22 Inches |
| Height | 6.77 Inches |
| Ampere Rating | 27A |
| Application | Used for Full-Voltage Starting and Stopping of AC Squirrel Cage Motors |
| Approvals | UL Listed File E78351 CCN NLDX - CSA Certified File LR60905 Class 3211 04 |
| Enclosure Type | Open |
| Horsepower Rating (3-Phase) | 7.5HP@200/230VAC - 10HP@460/575VAC |
| Maximum Voltage Rating | 600VAC |
| Number of Poles | 3-Pole |
| NEMA Size | 1 |
| Operating Voltage | 120VAC@60Hz - 110VAC@50Hz |
| Overload Type | Motor Logic (Class 20) |
| Phase | 3-Phase |
| Action | Non-Reversing |
| Terminal Type | Screw Clamp |
| Type | S |
| Weight | 5.5 Pounds |
| Width | 4.53 Inches |

Shipping and Ordering

| | |
|-------------------|---|
| Category | 21192 - Contactors/Starters, NEMA, Open/Enclosed (NEMA 1), Size 1 & 2 |
| Discount Schedule | CP1 |
| Article Number | 785901070818 |
| Package Quantity | 1 |
| Weight | 4.16 lbs. |
| Availability Code | Stock Item: This item is normally stocked in our distribution facility. |
| Returnability | Y |

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 05/27/2009 16:41:12