

# Micro Commercial Components Corp.

Complete Discrete Semiconductor Solutions

Part Number	1N5817
product family	SCHOTTKY BARRIER RECTIFIERS
package type	DO-41
VRM(PRV)	20V
Ifsm	25A
IF(AV)	1.0A
@Vf	0.45V
@If	1.0A
Trr	
IR	1.0mA
@VR	20V
Package Qty	Bulk: 1K/Box, 50K/Ctn; Tape: 5K/Reel, 20K/Ctn; T/B: 5K/Ammo Box, 50K/Ctn.

This product is listed under the following categories where you may find similar products: Diodes

Schottky Barrier Rectifiers



**Micro Commercial Components** 

## 1N5817 **THRU** 1N5819

## **Features**

- **Guard Ring Protection**
- Low Forward Voltage
- Low Power Loss For High Efficiency
- Case Material: Molded Plastic. UL Flammability
- Classification Rating 94V-0 and MSL rating 1 Lead Free Finish/RoHS Compliant (Note1) ("P"Suffix designates Compliant. See ordering information)

## Maximum Ratings

- Operating Temperature: -55°C to +125°C Storage Temperature: -55°C to +125°C
- Maximum Thermal Resistance; 80°C/W Junction To Ambient

MCC Part Number	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
1N5817	20V	14V	20V
1N5818	30V	21V	30V
1N5819	40V	28V	40V

### Flectrical Characteristics @ 25°C Unless Otherwise Specified


liecti icai characteristics @ 25 c oniess otherwise specified				
Average Forward Current	I <sub>F(AV)</sub>	1.0A	T <sub>A</sub> = 90°C	
Peak Forward Surge Current	I <sub>FSM</sub>	25A	8.3ms, half sine	
Maximum Instantaneous Forward Voltage 1N5817 1N5818 1N5819	V <sub>F</sub>	.45V .55V .60V	$I_{FM} = 1.0A;$ $T_J = 25^{\circ}C^{*}$	
Maximum DC Reverse Current At Rated DC Blocking Voltage	I <sub>R</sub>	1.0mA 10mA	$T_J = 25^{\circ}C$ $T_J = 100^{\circ}C$	
Typical Junction Capacitance	C <sub>j</sub>	110pF	Measured at 1.0MHz, V <sub>R</sub> =4.0V	

<sup>\*</sup>Pulse test: Pulse width 300 µsec, Duty cycle 2%

Note: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.

## 1 Amp Schottky **Barrier Rectifier** 20 to 40 Volts

DO-41



DIMENSIONS					
	INCH	HES	M	M	
DIM	MIN	MAX	MIN	MAX	NOTE
Α	.166	.205	4.10	5.20	
В	.080	.107	2.00	2.70	
С	.028	.034	.70	.90	
_	4.000				



## **Ordering Information**

Device	Packing
(Part Number)-TP	Tape&Reel 5Kpcs/Reel
(Part Number)-AP	Ammo Packing;5Kpcs/AmmoBox
(Part Number)-BP	Bulk;1Kpcs/Box

#### \*\*\*IMPORTANT NOTICE\*\*\*

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes.
Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp. and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*APPLICATIONS DISCLAIMER\*\*\*

Products offer by *Micro Commercial Components Corp* . are not intended for use in Medical,

Aerospace or Military Applications.