



## Model #: AVR550U

### AVR Series Line-Interactive UPS System - Affordable line-interactive protection for PCs and workstations



#### Highlights

- 550VA ultra-compact line-interactive UPS
- Maintains 120V nominal output over an input range of 83V to 147V
- Workstation-optimized features include USB port (HID-PDC compliant), single-line TEL / DSL surge suppression, 4 battery- and surge-protected outlets and 4 surge-only outlets (8 total)
- Space saving right-angle input plug
- Input: NEMA 5-15P (120V 15A) / Output: 8 NEMA 5-15R (120V)
- 2-year product warranty ,

#### Description

Tripp Lite's AVR550U line-interactive UPS offers complete protection for PCs, workstations and other sensitive electronics in an ultra-compact, mountable housing. Prevents data loss and system downtime by providing battery-supported AC output during blackouts and Automatic Voltage Regulation (AVR) during brownouts and overvoltages. 8 output receptacles, 2 of which are widely spaced to accommodate large transformer plugs without blocking outlets. 4 outlets feature full battery support and surge suppression, protecting computers, monitors and other vital system components from loss of power. 4 additional outlets with surge suppression only are ideal for printers and other peripherals not requiring battery support. Single-line telephone suppression jacks protect modems, fax machines, cordless phones and other equipment with standard dialup or DSL RJ-11 phone line connections. USB port with included cable and PowerAlert monitoring software enables safe unattended system shutdown in the case of extended power failure. HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X. Audible alarm and front panel LEDs offer status information regarding line and battery power operation. 550VA/300 watt power handling ability supports entry-level PCs for up to 17 minutes during power failures. 2-year warranty.

#### Applications

Basic PCs for home/home-office use, network workstations, audio/video equipment, home entertainment systems and other sensitive electronic devices.

#### Package Includes

- AVR550U UPS System
- PowerAlert Software, USB cable, Phone cable
- Instruction manual with warranty information

#### Features

- AVR550U line interactive UPS offers complete protection from blackouts, brownouts and surges on both AC and Tel/DSL line connections
- Built-in Automatic Voltage Regulation (AVR) boosts brownouts as low as 83 and reduces overvoltages up to 147 back to usable 120V nominal levels
- 8 outlets, two of which are widely spaced to accommodate large transformer plugs without blocking outlets
- 4 battery supported outlets protect computer, monitor and vital system peripherals, plus 4 additional surge suppression-only outlets for printers and other system accessories not requiring battery support
- Provides battery derived AC output during blackouts, voltage boost during brownouts and voltage reduction during overvoltages

550VA/300 watt power handling ability supports a variety of PCs, workstations and other sensitive electronics  
 Supports entry-level PC systems up to 17 minutes during blackout conditions  
 Built-in single line Tel/DSL line surge suppression protects modem, fax machine or cordless phone  
 USB port, PowerAlert software and cabling offer safe unattended shutdown without data loss during extended outages  
 HID compliant USB port enables integration with built-in power management and auto shutdown features of Windows and Mac OS X  
 Supports Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application/OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications  
 Hot swappable user battery replacement supported via battery access door  
 Space saving, ultra-compact housing fits almost anywhere  
 Keyhole mounting flanges enable secure wallmount installation

## Specifications

<b>SYSTEM OVERVIEW</b>	
<b>Voltage compatibility</b>	120VAC
<b>Frequency compatibility</b>	60Hz
<b>OUTPUT</b>	
<b>Output VA</b>	550
<b>Output watts</b>	300
<b>Output nominal voltage</b>	120VAC
<b>Output voltage regulation</b>	Sine wave 120V +8% / -21% (line mode) / PWM sine wave 115V +/-5% (battery mode)
<b>Output frequency regulation</b>	LINE MODE: Passes line frequency of 60Hz +/-10% BATTERY MODE: Inverter output regulated to 60Hz +/-0.5Hz
<b>Outlet quantity / type</b>	8 NEMA 5-15R
<b>INPUT</b>	
<b>Maximum input amps</b>	12A
<b>Input connection type</b>	NEMA 5-15P, right-angle plug
<b>Input cord length</b>	6ft / 1.8m
<b>Recommended Electrical Service</b>	120V 15A
<b>BATTERY</b>	
<b>Full load runtime</b>	3 minutes
<b>Half load runtime</b>	9 minutes
<b>DC system voltage</b>	12 VDC
<b>Typical battery lifespan</b>	3-6 years, depending on usage
<b>Battery recharge rate</b>	2-4 hours to 90%
<b>VOLTAGE REGULATION</b>	
<b>Voltage regulation description</b>	Automatic voltage regulation maintains 120V nominal over an input voltage range of 83 to 147
<b>Overvoltage correction</b>	Output voltage is reduced by 12% as line voltage increases to 128V or higher
<b>Brownout correction</b>	Output voltage is boosted by 14% as line voltage decreases to 104V or lower
<b>LEDS ALARMS &amp; SWITCHES</b>	
<b>Front panel LEDs</b>	2 LEDs indicate line power, battery power status
<b>Alarms</b>	Audible alarm beeps at regular intervals to indicate battery backup operation. Alarm also sounds during self-test operation. Alarm can be disabled altogether via PowerAlert software

Switches	Combination power off / on / self-test push button switch
<b>SURGE / NOISE SUPPRESSION</b>	
AC surge suppression	400 joules
Dataline suppression	Tel/DSL
EMI / RFI AC noise suppression	Yes
<b>PHYSICAL</b>	
Shipping weight (lbs)	14.25
Shipping weight (kg)	6.47
Shipping Dimensions (HWD/in)	4.75 x 13.5 x 8.75
Shipping Dimensions (HWD/cm)	12.07 x 34.29 x 22.23
Unit weight (lbs)	10.95
Unit weight (kg)	4.97
Unit Dimensions (HWD/in)	3.5 x 11.25 x 6
Unit Dimensions (HWD/cm)	8.89 x 28.56 x 15.24
Material of construction	ABS
Form factors supported	Ultra-compact
Battery Access	Hot-swappable batteries are accessible via battery door
<b>ENVIRONMENTAL</b>	
Operating Temperature	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
Storage Temperature	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
Relative Humidity	0 to 95%, non-condensing
<b>COMMUNICATIONS</b>	
Network monitoring port	USB (HID)
Software and cabling included	Includes USB cable and PowerAlert UPS monitoring software
WatchDog compatibility	Yes, compatible with Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application / OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications
<b>LINE / BATTERY TRANSFER</b>	
Transfer time from line power to battery mode	2-4 milliseconds
Low voltage transfer to battery power	Switches to battery power as line voltage drops to 83V or lower / Resets to AC mode as line voltage increases to 87V or higher
High voltage transfer to battery power	Switches to battery power as line voltage increases to 147V or higher / Resets to line power as line voltage drops to 143V or less
<b>SPECIAL FEATURES</b>	
Cold Start	Yes, inverter can be "cold started" to enable temporary AC output during a power failure
<b>CERTIFICATIONS</b>	
Certifications	Tested to UL1778 (USA), CSA C22.2 No. 107.3 (Canada), NOM (Mexico), Class B (Emissions), FCC Part 68 and Industry Canada (Telecommunications)