





Inductive Sensors



Housing Style	Part Number	ID Number	Features	Sensing Range (mm)	Output
30 mm - Nonembeddable, Potted-In Cable 	Ni 15-G30K-AN6X	T4671700	Short Barrel	15	3-Wire DC NPN
	Ni 15-G30K-AP6X	T4670700	Short Barrel	15	3-Wire DC PNP
	Ni 15-G30-Y0 Ni 15-G30-Y0X	T1006300 T4020100		15 15	2-Wire DC NAMUR
30 mm - Nonembeddable, Potted-In Cable 	Ni 15-G30-AN6X Ni 15-G30-AN7X	T4647700 T1714900		15 15	3-Wire DC NPN
	Ni 15-G30-AP6X	T4647600		15	3-Wire DC PNP
	Ni 20-G30-ADZ30X2	T4205404		20	2-Wire AC/DC Short-Circuit Protected
	Ni 15-G30-AZ3X	T1306000		15	2-Wire AC/DC

Voltage	Switching Freq. (Hz)	Operating Current AC/DC (mA)	Operating Temp. (°C)	Protection	Housing	Face	End Cap	Power LED	Output LED	Cable Length/ Cable /Mat.	Wiring Diagram #	Wiring Diagrams
10-30 VDC	500	≤200	-25 to +70	IP 67	CPB	PA 12	EPTR	N/A	YE	2M/PVC	1	<p>Diagram 1</p> 
10-30 VDC	500	≤200	-25 to +70	IP 67	CPB	PA 12	EPTR	N/A	YE	2M/PVC	2	<p>Diagram 2</p> 
5-30 VDC	200	Remote	-25 to +70	IP 67	CPB	PA 12	EPTR	N/A	N/A	2M/PVC	3	<p>Diagram 3</p> 
	200	Remote	-25 to +70	IP 67	CPB	PA 12	EPTR	N/A	YE	2M/PVC	3	
10-30 VDC	500	≤200	-25 to +70	IP 67	CPB	PA 12	EPTR	N/A	YE	2M/PVC	1	<p>Diagram 4</p> 
	500	≤200	-25 to +70	IP 67	CPB	PA 12	EPTR	N/A	YE	2M/PVC	1	
10-30 VDC	500	≤200	-25 to +70	IP 67	CPB	PA 12	EPTR	N/A	YE	2M/PVC	2	
20-250 VAC 10-300 VDC	20	≤400/300	-25 to +70	IP 67	CPB	PA 12	EPTR	GN	RD	2M/PVC	4	
20-250 VAC 10-300 VDC	20	≤400/300	-25 to +70	IP 67	CPB	PA 12	EPTR	N/A	RD	2M/PVC	4	

WIRING DIAGRAMS		LOCKNUT LN-M30		SPECIFICATIONS																																																						
<p>OUTPUT: AP6X</p>				<table border="1"> <tr><td>OPERATING VOLTAGE</td><td>10-30 VDC</td></tr> <tr><td>RIPPLE</td><td>≤10%</td></tr> <tr><td>DIFFERENTIAL TRAVEL (HYSTERESIS)</td><td>3-15% (5% TYPICAL)</td></tr> <tr><td>VOLTAGE DROP ACROSS CONDUCTING SENSOR</td><td>≤1.8 V at 200 mA</td></tr> <tr><td>OUTPUT FUNCTION</td><td>NORMALLY OPEN 3-WIRE DC SELF-CONTAINED</td></tr> <tr><td>TTL COMPATIBLE</td><td>NO</td></tr> <tr><td>SHORT-CIRCUIT PROTECTED</td><td>YES</td></tr> <tr><td>TRIGGER CURRENT FOR OVERLOAD PROTECTION</td><td>≥220 mA</td></tr> <tr><td>CONTINUOUS LOAD CURRENT</td><td>≤200 mA</td></tr> <tr><td>OFF-STATE (LEAKAGE) CURRENT</td><td><10 μA</td></tr> <tr><td>NO-LOAD CURRENT</td><td>5.5-9.5 mA</td></tr> <tr><td>TIME DELAY BEFORE AVAILABILITY</td><td>≤8 ms</td></tr> <tr><td>POWER-ON EFFECT PROTECTION</td><td>INCORPORATED</td></tr> <tr><td>REVERSE POLARITY PROTECTION</td><td>INCORPORATED</td></tr> <tr><td>WIRE-BREAK PROTECTION</td><td>INCORPORATED</td></tr> <tr><td>PROTECTION AGAINST TRANSIENTS</td><td>2 kV, 1 ms, 1 kΩ</td></tr> <tr><td>OPERATING TEMPERATURE</td><td>-25°C to +70°C (-13°F to +158°F)</td></tr> <tr><td>ENCLOSURE</td><td>MEETS NEMA 1, 3, 4, 6, 13 AND IEC IP67</td></tr> <tr><td>SHOCK</td><td>30 g, 11 ms</td></tr> <tr><td>VIBRATION</td><td>55 Hz, 1 mm AMPLITUDE (IN ALL 3 PLANES)</td></tr> <tr><td>LED FUNCTION</td><td>RED: OUTPUT ENERGIZED</td></tr> <tr><td>SENSING RANGE</td><td>15 mm = .591" (NOMINAL)</td></tr> <tr><td>SWITCHING FREQUENCY</td><td>500 Hz</td></tr> <tr><td>REPEATABILITY</td><td>≤2% of RATED OPERATING DISTANCE</td></tr> <tr><td>EMBEDDABLE (SHIELDED)</td><td>NO</td></tr> </table>		OPERATING VOLTAGE	10-30 VDC	RIPPLE	≤10%	DIFFERENTIAL TRAVEL (HYSTERESIS)	3-15% (5% TYPICAL)	VOLTAGE DROP ACROSS CONDUCTING SENSOR	≤1.8 V at 200 mA	OUTPUT FUNCTION	NORMALLY OPEN 3-WIRE DC SELF-CONTAINED	TTL COMPATIBLE	NO	SHORT-CIRCUIT PROTECTED	YES	TRIGGER CURRENT FOR OVERLOAD PROTECTION	≥220 mA	CONTINUOUS LOAD CURRENT	≤200 mA	OFF-STATE (LEAKAGE) CURRENT	<10 μA	NO-LOAD CURRENT	5.5-9.5 mA	TIME DELAY BEFORE AVAILABILITY	≤8 ms	POWER-ON EFFECT PROTECTION	INCORPORATED	REVERSE POLARITY PROTECTION	INCORPORATED	WIRE-BREAK PROTECTION	INCORPORATED	PROTECTION AGAINST TRANSIENTS	2 kV, 1 ms, 1 kΩ	OPERATING TEMPERATURE	-25°C to +70°C (-13°F to +158°F)	ENCLOSURE	MEETS NEMA 1, 3, 4, 6, 13 AND IEC IP67	SHOCK	30 g, 11 ms	VIBRATION	55 Hz, 1 mm AMPLITUDE (IN ALL 3 PLANES)	LED FUNCTION	RED: OUTPUT ENERGIZED	SENSING RANGE	15 mm = .591" (NOMINAL)	SWITCHING FREQUENCY	500 Hz	REPEATABILITY	≤2% of RATED OPERATING DISTANCE	EMBEDDABLE (SHIELDED)	NO			
OPERATING VOLTAGE	10-30 VDC																																																									
RIPPLE	≤10%																																																									
DIFFERENTIAL TRAVEL (HYSTERESIS)	3-15% (5% TYPICAL)																																																									
VOLTAGE DROP ACROSS CONDUCTING SENSOR	≤1.8 V at 200 mA																																																									
OUTPUT FUNCTION	NORMALLY OPEN 3-WIRE DC SELF-CONTAINED																																																									
TTL COMPATIBLE	NO																																																									
SHORT-CIRCUIT PROTECTED	YES																																																									
TRIGGER CURRENT FOR OVERLOAD PROTECTION	≥220 mA																																																									
CONTINUOUS LOAD CURRENT	≤200 mA																																																									
OFF-STATE (LEAKAGE) CURRENT	<10 μA																																																									
NO-LOAD CURRENT	5.5-9.5 mA																																																									
TIME DELAY BEFORE AVAILABILITY	≤8 ms																																																									
POWER-ON EFFECT PROTECTION	INCORPORATED																																																									
REVERSE POLARITY PROTECTION	INCORPORATED																																																									
WIRE-BREAK PROTECTION	INCORPORATED																																																									
PROTECTION AGAINST TRANSIENTS	2 kV, 1 ms, 1 kΩ																																																									
OPERATING TEMPERATURE	-25°C to +70°C (-13°F to +158°F)																																																									
ENCLOSURE	MEETS NEMA 1, 3, 4, 6, 13 AND IEC IP67																																																									
SHOCK	30 g, 11 ms																																																									
VIBRATION	55 Hz, 1 mm AMPLITUDE (IN ALL 3 PLANES)																																																									
LED FUNCTION	RED: OUTPUT ENERGIZED																																																									
SENSING RANGE	15 mm = .591" (NOMINAL)																																																									
SWITCHING FREQUENCY	500 Hz																																																									
REPEATABILITY	≤2% of RATED OPERATING DISTANCE																																																									
EMBEDDABLE (SHIELDED)	NO																																																									
		<table border="1"> <tr> <td>MATERIAL</td> <td>BRASS BARREL</td> <td rowspan="2">3RD ANGLE PROJECTION</td> <td rowspan="2"> </td> <td rowspan="2"> TURCK INC </td> </tr> <tr> <td>FINISH</td> <td>COPPER/NICKEL/ CHROME PLATING</td> </tr> <tr> <td>DRWN</td> <td>SMW</td> <td>DATE</td> <td>3/18/87</td> <td>PART NO.</td> <td>Ni15-G30-AP6X</td> </tr> <tr> <td>CHKD</td> <td></td> <td>DATE</td> <td></td> <td></td> <td></td> </tr> <tr> <td>TMI</td> <td></td> <td></td> <td></td> <td>SIZE</td> <td>B</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>ID NO.</td> <td>4647600</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>SCALE</td> <td>NONE</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>BMPC-DC\4647600</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>SHEET</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>OF</td> </tr> </table>		MATERIAL	BRASS BARREL	3RD ANGLE PROJECTION		TURCK INC	FINISH	COPPER/NICKEL/ CHROME PLATING	DRWN	SMW	DATE	3/18/87	PART NO.	Ni15-G30-AP6X	CHKD		DATE				TMI				SIZE	B					ID NO.	4647600					SCALE	NONE						BMPC-DC\4647600						SHEET						OF
MATERIAL	BRASS BARREL	3RD ANGLE PROJECTION		TURCK INC																																																						
FINISH	COPPER/NICKEL/ CHROME PLATING																																																									
DRWN	SMW	DATE	3/18/87	PART NO.	Ni15-G30-AP6X																																																					
CHKD		DATE																																																								
TMI				SIZE	B																																																					
				ID NO.	4647600																																																					
				SCALE	NONE																																																					
					BMPC-DC\4647600																																																					
					SHEET																																																					
					OF																																																					
<table border="1"> <tr> <td>C</td> <td>SEE REVISION DOCUMENT 4647600</td> <td>SWC</td> <td>8/1/94</td> <td></td> </tr> <tr> <td>REV</td> <td>DESCRIPTION</td> <td>DRFT</td> <td>DATE</td> <td>CHKD</td> </tr> <tr> <td colspan="5" style="text-align: center;">REVISIONS</td> </tr> </table>		C	SEE REVISION DOCUMENT 4647600	SWC	8/1/94		REV	DESCRIPTION	DRFT	DATE	CHKD	REVISIONS					<p>DIMENSIONS ARE IN <u>INCHES</u> mm</p>		<p>SCALE NONE BMPC-DC\4647600 SHEET OF</p>																																							
C	SEE REVISION DOCUMENT 4647600	SWC	8/1/94																																																							
REV	DESCRIPTION	DRFT	DATE	CHKD																																																						
REVISIONS																																																										