Solutions for Electronic Specialty Markets (ESM)

- **Product Catalog for Electronic Specialty Markets**
  - **3M™ Electronic Specialty Markets - New Product Releases**
  - **3M™ Abrasives**
  - **3M™ Adhesives, Cleaners & Compounds**
  - **3M™ Breadboards & Test Clips**
  - **3M™ Cable & Assemblies**
  - **3M™ Copper Interconnects**
  - **3M™ Fiber Optics**
  - **3M™ Fire Protection**
  - **3M™ Heat Shrink**
  - **3M™ Identification Systems**
  - **3M™ Occupational Health & Safety Products**
  - **3M™ Protective Bumpers**
  - **3M™ Reclosable Fasteners**
  - **3M™ Splicing, Terminating & Ducting**
  - **3M™ Static Control**
  - **3M™ Tapes**
  - **3M™ Terminals, Kits & Tools**
  - **3M™ Vacuums & Accessories**
  - **3M™ Warehousing & Packaging Supplies**
  - **3M™ Wire Connectors**

- **Other Tools**
  - **What's New**
  - **Sales Contacts**
  - **U.S. Distributors**
- **Search This Product Catalog**

🖶 Printer-friendly format **3M™ D Sub Connector Plastic Junction Shell, 3485-2100R**
9 contacts, Round cable type, 100/Pack

[click to enlarge]

3M Id : 80-6101-8219-0
GTIN(UPC/EAN) : 0 00 54007 36336 1

Additional Information

· Uses standard hardware
· Light weight, compact size
· Full family of sizes
· RoHS compliant

For more information, refer to TS0037 (TS-0037).

Learn More . . .

Packaging Data
3M™ D Sub Junction Shell, Plastic, TS0037 - Data Sheet (PDF 563.5 K)

Please Note:
Adobe® Acrobat® Reader is required to view PDF documents.

Get Acrobat Reader

Characteristics

Color	Gray
Insulation Flammability Rating	UL 94V-0
Mounting Option	Mounting Flanges - 2-56 Threaded
Number of Contacts	9
Primary Trademark Name	3M
Shell Material	Glass Filled Polyester (PBT)