



### Technical Characteristics

|                          |  |
|--------------------------|--|
| Catalog Reference Number | 8501CT9601   |
| Approvals                | UL Listed File: E78403 CCN NKCR - CSA Certified File: LR60905 Class 321103 - CE Marked                       |
| Ampere Rating            | 10A  |
| Application              | Heavy-duty design with modular construction  |
| Terminal Type            | Screw Clamp  |
| Type                     | X  |
| Height                   | 3.50 Inches  |
| Relay Type               | Control  |
| Depth                    | 3.95 Inches  |
| Width                    | 2.23 Inches  |
| Phase                    | 1-Phase  |
| Number of Poles          | 2-Pole   |
| Maximum Voltage Rating   | 600VAC   |
| Mounting Type            | Panel  |
| Operating Times          | Pick-Up: 15ms - Drop-Out: 16ms   |
| Contact Configuration    | 2 N.O.   |
| Features                 | Straight-through wiring; Plug-in contact cartridges; Self-lifting pressure wire connectors; Replaceable coil |
| Coil Voltage             | 110VAC@50Hz - 120VAC@60Hz  |
| Contact Rating           | A600   |
| Weight                   | 2.0 Pounds   |

### Shipping and Ordering

|                   |   |
|-------------------|---|
| Category          | 21158 - Relays, Industrial Control, NEMA, AC, Type XO                   |
| Discount Schedule | CP1   |
| Article Number    | 785901536963  |
| Package Quantity  | 1   |
| Weight            | 2.12 lbs.   |
| Availability Code | Stock Item: This item is normally stocked in our distribution facility. |
| Returnability     | Y   |

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 05/26/2009 17:05:17