

## Model: ACD-14 TRMS PLUS 600A Clamp-On Multimeter with Dual Display

[Home](#)



The ACD-14 TRMS-PLUS is the professionals' choice for both HVAC & Electrical applications due to its complete set of measuring features. Its dual displays allows viewing amperage and voltage simultaneously. True RMS voltage and current measurements for more precise results when measuring in noisy AC environments.

- Dual Displays – Permits simultaneous reading of Amperage & Voltage
- True RMS for precise measurement results
- New thin jaws, 5mm thinner than others to access tight measurement spaces
- Micro Amps measurement for testing Flame Sensors
- Capacitance to 3000  $\mu$ F
- Temperature with Type-K Thermocouple probe
- AC and DC Voltage to 600V
- Resistance to 40M $\Omega$
- AC Current to 600A
- Frequency measurement
- Diode test and Continuity Buzzer
- Hold and Maximum reading functions
- In rush current
- Accommodates conductors up to 28 mm (1.1") in diameter
- Auto ranging
- Auto power off and low battery indication
- Rubber over-molded case



### FEATURES

<b>Battery Life:</b>	95 hours approx. (in DCV mode)
<b>Size:</b>	L190mm X W 63mm X H 32mm (L 7.48" X W 2.48" X H 1.25")
<b>Weight:</b>	204 g (0.450 lb approx.)
<b>Safety:</b>	CE EN61010-1, EN61010-2-032 - Pollution Degree 2
<b>Instruction Manual:</b>	<a href="#">Yes</a>
<b>Detailed Specs:</b>	<a href="#">Yes</a>
<b>Hi-Resolution Image:</b>	<a href="#">Yes</a>

### SPECIFICATIONS

<b>Display:</b>	3-3/4 digits 4000 counts, dual LCD displays
<b>Update Rate:</b>	3 per second nominal
<b>Polarity:</b>	Automatic
<b>Low Battery Indication:</b>	0°C to 40°C (32°F to 104°F)
<b>Power Supply:</b>	Two 3V alkaline button batteries (ANSI/NEDA-5004LC, IEC-CR2032)

### OPTIONAL ACCESSORIES

Part Number	Description
<a href="#">ELS2A</a>	AC Current Clamp Accessory
<a href="#">ACF-3000AK</a>	3000A Flexible Current Transducer
<a href="#">TA-1A</a>	K-type thermocouple, temperature adapter
<a href="#">TL36A</a>	Test leads with threaded alligator clips