



List Price \$233.00 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.**

### Technical Characteristics

Total Travel	90°
Operating Torque/Force	3 Inch-Pounds
Basic Switch (Plug-In Unit)	Standard
Actuator	Wire Extension
Actuation	Any Direction
Turret Head	Wobble Stick
Plug-In Receptacle	Standard
Actuator Action	Spring Return
Differential Travel	3°
Pre-Travel	10°
Approvals	UL Listed - CSA Certified - CE Marked
Body Material	Zinc Alloy
Connection Type	0.5 Inch NPT Conduit Entrance (screw clamp terminals)
Contact Rating	NEMA A600/Q600
Contact Operation	Snap Action
Contact Material	Silver Alloy
Contact Configuration	1 NO/1 NC
Contact Form	Form Z - SPDT-DB
Pilot Light	None
Ampere Rating	10A
Maximum Voltage Rating	600V
Type	C
Operating Temperature Range	0°F to 185°F
Type of Duty	Heavy Duty

### Shipping and Ordering

Category	21499 - Limit Switches, Heavy Duty, Type C
Discount Schedule	CP1
GTIN	00785901542117
Package Quantity	1
Weight	1.35 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y

Generated: 06/14/2011 01:49:46

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.