8910DPA73V14

Definite Purpose Contactor , Non-Reversing, 75A, 3-Phase, 3-Pole





Technical Characteristics

Enclosure Type Open Ampere Rating 75A Approvals UL Listed - CSA Certified - CE Marked Horsepower Rating (1-Phase) 5HP@115VAC - 15HP@230VAC Maximum Voltage Rating 600VAC Mounting Type Panel Number of Poles 3-Pole Locked Rotor Amperes 450A@230VAC - 375A@460VAC - 300A@575VAC Horsepower Rating (3-Phase) 25HP@230VAC - 40HP@460/575VAC Operating Voltage 24VAC@50/60Hz Phase 3-Phase Action Non-Reversing Type DPA Depth 4.37 Inches Height 5.20 Inches Width		
Approvals Horsepower Rating (1-Phase) 5HP@115VAC - 15HP@230VAC Maximum Voltage Rating 600VAC Mounting Type Panel Number of Poles 3-Pole Locked Rotor Amperes 450A@230VAC - 375A@460VAC - 300A@575VAC Horsepower Rating (3-Phase) 25HP@230VAC - 40HP@460/575VAC Operating Voltage 24VAC@50/60Hz Action Non-Reversing Type DPA Depth Height Height	Enclosure Type	Open
Horsepower Rating (1-Phase) Maximum Voltage Rating 600VAC Mounting Type Panel Number of Poles Locked Rotor Amperes 450A@230VAC - 375A@460VAC - 300A@575VAC Horsepower Rating (3-Phase) 25HP@230VAC - 40HP@460/575VAC Operating Voltage 24VAC@50/60Hz Phase Action Non-Reversing Type DPA Depth Height 520 Inches	Ampere Rating	75A
Maximum Voltage Rating600VACMounting TypePanelNumber of Poles3-PoleLocked Rotor Amperes450A@230VAC - 375A@460VAC - 300A@575VACHorsepower Rating (3-Phase)25HP@230VAC - 40HP@460/575VACOperating Voltage24VAC@50/60HzPhase3-PhaseActionNon-ReversingTypeDPADepth4.37 InchesHeight5.20 Inches	Approvals	UL Listed - CSA Certified - CE Marked
Mounting Type Panel Number of Poles 3-Pole Locked Rotor Amperes 450A@230VAC - 375A@460VAC - 300A@575VAC Horsepower Rating (3-Phase) 25HP@230VAC - 40HP@460/575VAC Operating Voltage 24VAC@50/60Hz Phase 3-Phase Action Non-Reversing Type DPA Depth 4.37 Inches Height 5.20 Inches	Horsepower Rating (1-Phase)	5HP@115VAC - 15HP@230VAC
Number of Poles 3-Pole Locked Rotor Amperes 450A@230VAC - 375A@460VAC - 300A@575VAC Horsepower Rating (3-Phase) 25HP@230VAC - 40HP@460/575VAC Operating Voltage 24VAC@50/60Hz Phase 3-Phase Action Non-Reversing Type DPA Depth 4.37 Inches Height 5.20 Inches	Maximum Voltage Rating	600VAC
Locked Rotor Amperes 450A@230VAC - 375A@460VAC - 300A@575VAC Horsepower Rating (3-Phase) 25HP@230VAC - 40HP@460/575VAC Operating Voltage 24VAC@50/60Hz Phase 3-Phase Action Non-Reversing Type DPA Depth 4.37 Inches Height 5.20 Inches	Mounting Type	Panel
Horsepower Rating (3-Phase) 25HP@230VAC - 40HP@460/575VAC Operating Voltage 24VAC@50/60Hz Phase 3-Phase Action Non-Reversing Type DPA Depth 4.37 Inches Height 5.20 Inches	Number of Poles	3-Pole
Operating Voltage 24VAC@50/60Hz Phase 3-Phase Action Non-Reversing Type DPA Depth 4.37 Inches Height 5.20 Inches	Locked Rotor Amperes	450A@230VAC - 375A@460VAC - 300A@575VAC
Phase 3-Phase Action Non-Reversing Type DPA Depth 4.37 Inches Height 5.20 Inches	Horsepower Rating (3-Phase)	25HP@230VAC - 40HP@460/575VAC
Action Non-Reversing Type DPA Depth 4.37 Inches Height 5.20 Inches	Operating Voltage	24VAC@50/60Hz
Type DPA Depth 4.37 Inches Height 5.20 Inches	Phase	3-Phase
Depth 4.37 Inches Height 5.20 Inches	Action	Non-Reversing
Height 5.20 Inches	Туре	DPA
	Depth	4.37 Inches
Width 3.39 Inches	Height	5.20 Inches
	Width	3.39 Inches

Shipping and Ordering

Category	21347 - Contactors, Definite Purpose, 75 Amp
Discount Schedule	CP1B
GTIN	00785901118350
Package Quantity	1
Weight	3.68 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Υ
Country of Origin	MX

document.

Generated: 11/23/2009 15:47:17

