SMD030F-2018-2 Product Details



SMD030F-2018-2

TE Part Number: F94061-000



PolySwitch Resettable Devices



Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Surface Mount Application
- Family Name = SMD
- Surface Mount Construction
- IH (Room Temperature) = .3 Amps.
- IT (Room Temperature) = .80 Amps.

View all Features | Find Similar Products

Documentation & Additional Information

Product Drawings:

• <u>SMD030F-2018</u> (PDF, English)

Catalog Pages/Data Sheets:

• None Available

Product Specifications:

• None Available

Application Specifications:

• None Available

Instruction Sheets:

• None Available

CAD Files:

• None Available

Additional Information:

• Product Line Information

Related Products:

• Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- UL Recognized = 180800-E74889
- CSA File No. = 1031175 (CA 78165-1)

Electrical Characteristics:

- IH (Room Temperature) (Amps.) = 0.3
- IT (Room Temperature) (Amps.) = 0.80
- $\underline{\text{Vmax Operating (V)}} = 60$
- Rmin (•) = 0.50
- <u>R1 Max [Post Trip] (•)</u> = 2.30
- <u>UL Rated Current (Amps.)</u> = 20
- Tripped Power Dissipation (Typical) (W) = 0.90

Termination Related Features:

• Construction = Surface Mount

Contact Related Features:

• Family Name = SMD

Configuration Related Features:

- Form Factor (inches) = 2018
- <u>Form Factor (mm)</u> = 5050

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant
- TUV Certificate No. = R72041427

Conditions for Usage:

• Operating Temperature (Max.) (°C) = 85

Operation/Application:

• Application = Surface Mount

Packaging Related Features:

• Packaging Method = Tape & Reel

Other:

• Brand = Raychem