

Part Number: **5922222002F**

### General Description

Series	592
Configuration	3 mm Lens
Description	Hi Int. Green/Hi Int. Green 3mm Bi-Level Prism CBI Surface Mount LED
Package Options	Sample Strip
Sizes	3mm
Lamp Type	Single Color
Compliance	UL 94V-0

### Absolute Maximum Ratings (Ta = 25°)

Forward Current mA	30mA
Forward Current Pulsed	120mA
Solder Temperature	235 peak, above 185 for 90 sec, 215 for 3 min
Operating Temperature	-55 +100
Storage Temperature	-55 +100

### Operating Characteristics

Color	G-G
LED Type	High Intensity
LED Position	1,2
Luminous Intensity Typical	9.1
Dominant Wavelength Typical	569nm
Power Dissipation Max	100mWmW




This is a  
RoHS Compliant Product  
To learn more click here





# 592 SERIES


3mm Bi-level Prism® CBI®  
Surface Mount LED  
BRIGHT SINGLE COLOR



## FEATURES / BENEFITS


- ▲ Available as a Lead (Pb) Free product - RoHS Compliant.
- ▲ Incorporates latest LED technology, specifically designed for surface mounting.
- ▲ Compatible with automatic placement equipment.
- ▲ Compatible with surface mount reflow soldering processes.
- ▲ Black housing enhances contrast ratio.
- ▲ Housing material meet UL-94V-0 flammability ratings.
- ▲ Patented Bi-level design provides increased indication without increased space.
- ▲ Illumination areas compatible with industry standard 3mm through-hole Bi-level Circuit Board Indicators.
- ▲ Packaged in moisture barrier bags for dry packaging per IPC/JEDEC J-STD-033.
- ▲ Helps to eliminate mixed technology pc board processing.

## SPECIFICATIONS




++ SINGLE COLOR LED SHOWN ++

### PART NUMBER CODE\*



PART NUMBER *	COLOR COMBO
592-2121-0XX	AlGaAs Red/AlGaAs Red
592-2222-0XX	GREEN/GREEN
592-2727-0XX	AllnGaP Yellow/AllnGaP Yellow

\* Part Number with "F" suffix ending is a Lead (Pb) Free Product - RoHS Compliant.





## 3mm Bi-level Prism<sup>®</sup> CBI<sup>®</sup> Surface Mount LED

### ABSOLUTE MAXIMUM RATINGS (T<sub>A</sub>= 25°C)

Parameter	21	22	27
COLOR	AlGaAs Red	Green	AllnGaP Yellow
POWER DISSIPATION (derate linearly from 25°C mW/°C)	100mW 0.8	100mW 0.6	100mW 0.6
FORWARD DC CURRENT	40mW	30mW	50mW
PEAK FORWARD CURRENT (10 µsec)	200mW	120mW	160mW
OPERATING TEMPERATURE	-55°C to +100°C		
STORAGE TEMPERATURE	-55°C to +100°C		
SOLDERING TEMPERATURES CONVECTION IR VAPOR PHASE	235°C Peak, above 185°C for 90 sec., 215°C for 3 min.		

### OPERATING CHARACTERISTICS (T<sub>A</sub>= 25°C)

Parameters	Part No.	Color	Min	Typ	Max	Units	Test Cond.
FORWARD VOLTAGE V <sub>F</sub>	21	AlGaAs Red		1.8	2.4	V	I <sub>F</sub> =10mA
	22	Green		2.1	2.6		
	27	AllnGaP Yellow		2	2.4		
REVERSE VOLTAGE V <sub>R</sub>	21	AlGaAs Red	5			V	I <sub>F</sub> =10µA
	22	Green	5				
	27	AllnGaP Yellow	5				
DOMINANT WAVELENGTH Dom	21	AlGaAs Red		638		nm	
	22	Green		569			
	27	AllnGaP Yellow		595			
LUMINOUS INTENSITY I <sub>v</sub>	21	AlGaAs Red		23.9		mcd	I <sub>F</sub> =10mA
	22	Green		9.1			
	27	AllnGaP Yellow		33.6			
VIEWING ANGLE (2θ <sub>1/2</sub> )	21	AlGaAs Red				deg.	
	22	Green					
	27	AllnGaP Yellow					

DIALIGHT RESERVES THE RIGHT TO MAKE CHANGES AT ANY TIME IN ORDER TO SUPPLY THE BEST PRODUCT POSSIBLE.



A4703



ISO 9001

Dialight Corporation

MDEF592D001\_B