

Model #: RS1215-HG

Power Strip - With Hospital-Grade Plug & Receptacles



Highlights

Designed for standard 19-inch racks (1U high) 12 hospital-grade outlets (6 front / 6 rear) 15-ft. cord with hospital-grade plug 15A resettable circuit breaker Illuminated On/Off switch with locking safety cover

Description

Tripp Lite's RS flanges are con meeting E power in rack enclo

cord and lighted switch with cover to prevent accidental turn-off.

PLUG/OUTLETS: NEMA 5-15P-HG hospital-grade plug and 12 NEMA 5-15R-HG hospital-grade outlets (6 front/6 rear)

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: 19-in. rackmount (1U)

Applications

AC power dis□ hospital-grade receptacles.

Package Includes

RS-1215-HG Rackmount Power Strip Instruction manual with warranty information

Features

Versatile

Uses one rack space (1U) in standard 19-in. rack ("zero U" mounting possible in many racks) 12 x NEMA 5-15R-HG hospital-grade output receptacles (6 front/6 rear), each pair with green-dot hospital-grade designation 15-ft. 14-gauge AC cord with high-impact resistant NEMA 5-15P-HG hospital-grade plug Lighted power switch (with safety cover) confirms power on/off status Snap-in switch guard prevents accidental turn-off 15A electrical capacity with resettable circuit breaker 120V AC, 50/60Hz electrical compatibility

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120VAC
Frequency compatibility	50/60Hz
OUTPUT	
Output volt amp capacity (amps)	15A
Outlet quantity / type	12 x NEMA 5-15R-HG Hospital Grade
Outlet orientation	6 front / 6 rear
INPUT	
Input connection type	NEMA 5-15P-HG Hospital Grade
Input cord length (ft.)	15
Input cord length (m)	4.572
Recommended Electrical Service	15A 120V
LEDS ALARMS & SWITCHES	
Switches	Red illuminated 2 positon switch controls power to all outlets
Locking switch cover	Transparent locking switch cover prevents accidental shutoff
PHYSICAL	
Unit weight (Ibs)	4.6
Unit Dimensions (HWD/in)	1.75 x 17.3 x 4
Unit Dimensions (HWD/cm)	4.4 x 43.9 x 10.2
Material of construction	Sheet metal
Form factors supported	1U rackmount, wallmount and undercounter installation supported
Receptacle Color	White
AC line cord color	Black
SPECIAL FEATURES	
TVSS grounding	Back panel nut and bolt grounding lug
CERTIFICATIONS	
UL1363 (Power Tap)	UL1363 (UR status) (Series Number: AGIP120V6IPRM)
cUL / CSA (Canada)	cUL (Series Number: AGIP120V6IPRM)
WARRANTY	
Product warranty	Lifetime