

Current refinements (click to remove)

[Search Tips](#) 
 Region [USA](#) Product Family [Locking Fork Terminal, Vinyl Insulated – Funnel Entry](#) Text Search: 'PV18-10LF-CY'

Your search criteria matched only one product, shown below.


- Locks in place for secure connection
- Fork design provides for fast and easy installation, without the need to remove fastener
- Insulation support helps to prevent wire damage in bending applications
- UL Flammability UL 94V-0, maximum insulation temperature 221°F (105°C)
- Internal barrel serrations assure good wire contact and maximum tensile strength
- UL and CSA rated to 600 V per UL 486

‡UL and CSA approved tooling/product combinations.

Part Number:	PV18-10LF-CY
RoHS Compliance Status:	Compliant
Note:	PV18-10LF-CY replaces PV18-10LF-C
Part Description:	Locking Fork Terminal, vinyl insulated, funnel entry, 22 – 18 AWG, #10 stud size.
Product Type:	Terminals
CSA Certified:	Yes
UL Listed:	Yes
Length (In.):	.97
Width (In.):	.33
Clearance:	.25
Max. Ins.:	.150
Panduit Color Code:	Red
Stock:	.03
Stud Size:	#10
Tool:	CT-100A‡, CT-600-A‡, CT-1550‡, CT-1551‡, CT-2500‡
Wire Range:	22 – 18 AWG
Min. Order UOM:	PC
Min. Order Qty.:	100
BOM Qty. (# of Pkgs.)	

[Add to My Catalog](#)

 Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'My Catalog' features.

