



## Technical Characteristics

Approvals	UL Listed - CSA Certified - IEC Rated
Catalog Reference Number	0611CT0401
Circuit Breaker Type	Standard
For Use With	Industrial Enclosures and Switchboards
General Application	Provides overload and short circuit protection
AC Magnetic Trip Setting	350A - 750A Adjustable Trip
Ampere Rating	30A
Frame Type	H-Frame
HACR Rated	Yes
Marketing Trade Name	Powerpact
Voltage Rating	600VAC/250VDC
Mounting Type	Unit Mount
Number of Poles	3-Pole
Weight	5 Pounds
Short Circuit Current Rating	25kA@240VAC - 18kA@480VAC - 14kA@600VAC
Terminal Type	Line: Lug - Load: Lug
Type	HD
Wire Size	#14-3/0 AWG(Al/Cu)
Height	6.40 Inches
Width	4.12 Inches
Depth	4.36 Inches

## Shipping and Ordering

Category	01110 -
Discount Schedule	DE2
Article Number	785901706632
Package Quantity	1
Weight	4.06 lbs.
Availability Code	Non-Stock Item: This item is not normally stocked in our distribution facility.
Returnability	Y

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 06/01/2009 15:14:38