



# Micro Commercial Components Corp.

Complete Discrete Semiconductor Solutions

Product Catalog > [Diodes](#) > [Switching Diodes](#) >

Part Number	BAS19
product family	SMALL SIGNAL DIODES
package type	SOT-23
VRM(PRV)	120V
Ifsm	0.5A
IF(AV)	200mA
@Vf	1.25V
@If	200mA
Trr	50nS
IR	100nA
@VR	120V
Package Qty	Tape : 3K/Reel, 30k/Box, 120K/Ctn;

This product is listed under the following categories where you may find similar products:  
[Diodes](#)  
[Switching Diodes](#)

# BAS19 THRU BAS21

## Small Signal Diodes 250mW

### Features

- Ideally Suited for Automatic Insertion
- 150°C Junction Temperature
- Fast Switching speed
- Epitaxial Planar Die Construction

### Mechanical Data

- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0 and MSL Rating 1
- Weight: 0.008 grams ( approx.)


MCC Part Number	Marking	Continuous Reverse Voltage $V_R$ (V)	Repetitive Peak Reverse Voltage $V_{RRM}$ (V)
BAS19	JP	100	120
BAS20	JR	150	200
BAS21	JS	200	250


### Maximum Ratings @ 25°C Unless Otherwise Specified

Parameter	Symbol	Value	Unit
Non-repetitive Peak Forward Current @ $t=1\mu s$	$I_{FSM}$	2.5	A
Forward Surge Current @ $t=1s$		0.5	A
Average Rectified Forward Current	$I_{F(AV)}$	200 <sup>(1)</sup>	mA
Forward DC Current at $T_{amb}=25^\circ C$	$I_F$	200 <sup>(2)</sup>	mA
Repetitive Peak Forward Current	$I_{FRM}$	625	mA
Power Dissipation up to $T_{amb}=25^\circ C$	$P_{tot}$	250	mW
Thermal Resistance Junction to Ambient	$R_{\theta JA}$	430	°C/W
Operating & Storage Temperature	$T_j, T_{STG}$	-65~150	°C


- Notes:** (1) Measured under pulse conditions;  
Pulse time =  $t_p \leq 0.3ms$   
(2) Device on fiberglass substrate,  
See layout on next page

### SOT-23





Top View



Suggested Solder Pad Layout

DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.110	.120	2.80	3.04	
B	.083	.098	2.10	2.64	
C	.047	.055	1.20	1.40	
D	.035	.041	.89	1.03	
E	.070	.081	1.78	2.05	
F	.018	.024	.45	.60	
G	.0005	.0039	.013	.100	
H	.035	.044	.89	1.12	
J	.003	.007	.085	.180	
K	.015	.020	.37	.51	

# BAS19 thru BAS21



## Electrical Characteristics

(T<sub>J</sub> = 25°C unless otherwise noted)


Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Forward Voltage	V <sub>F</sub>	I <sub>F</sub> = 100mA	—	—	1.0	V
		I <sub>F</sub> = 200mA	—	—	1.25	V
Leakage Current	I <sub>R</sub>	V <sub>R</sub> = V <sub>Rmax</sub>	—	—	100	nA
		V <sub>R</sub> = V <sub>Rmax</sub> ; T <sub>j</sub> = 150°C	—	—	100	μA
Dynamic Forward Resistance	r <sub>f</sub>	I <sub>F</sub> = 10mA	—	5	—	Ω
Capacitance	C <sub>tot</sub>	V <sub>R</sub> = 0 f = 1MHz	—	—	5	pF
Reverse Recovery Time (see figures)	t <sub>rr</sub>	I <sub>F</sub> = 30mA, I <sub>R</sub> = 30mA I <sub>rr</sub> = 3mA, R <sub>L</sub> = 100Ω	—	—	50	ns

(1) Device on fiberglass substrate, see layout (SOT-23).

## Test Circuit and Waveforms (BAS19, BAS20, BAS21)




Input Signal	- total pulse duration - duty factor - rise time of reverse pulse - reverse pulse duration	tp(tot) = 2μs δ = 0.0025 tr = 0.6ns tp = 100ns
Oscilloscope	- rise time - circuit capacitance*	tr = 0.35ns C < 1pF



\*C = oscilloscope input capacitance + parasitic capacitance

## Layout for R<sub>θJA</sub> test

Thickness: Fiberglass 0.059 in. (1.5 mm)  
Copper leads 0.012 in. (0.3 mm)





Micro Commercial Components

## Ordering Information

Device	Packing
(Part Number)-TP	Tape&Reel;3Kpcs/Reel

### \*\*\*IMPORTANT NOTICE\*\*\*

*Micro Commercial Components Corp* .reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes .  
*Micro Commercial Components Corp* .does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp* .and all the companies whose products are represented on our website, harmless against all damages.

### \*\*\*APPLICATIONS DISCLAIMER\*\*\*

Products offer by *Micro Commercial Components Corp* . are not intended for use in Medical, Aerospace or Military Applications.