

# HFA30PB120


Ultrafast, Soft Recovery Diode

## Features


- Ultrafast Recovery
- Ultrasoft Recovery
- Very Low  $I_{RRM}$
- Very Low  $Q_{rr}$
- Guaranteed Avalanche
- Specified at Operating Conditions

## Benefits

- Reduced RFI and EMI
- Reduced Power Loss in Diode and Switching Transistor
- Higher Frequency Operation
- Reduced Snubbing
- Reduced Parts Count



$V_R = 1200V$
$V_F(\text{typ.})^* = 2.3V$
$I_{F(AV)} = 30A$
$Q_{rr}(\text{typ.}) = 120nC$
$I_{RRM}(\text{typ.}) = 4.7A$
$t_{rr}(\text{typ.}) = 47ns$
$di_{(rec)M}/dt(\text{typ.})^* = 240A/\mu s$



## Description

International Rectifier's HFA16PB120 is a state of the art center tap ultra fast recovery diode. Employing the latest in epitaxial construction and advanced processing techniques it features a superb combination of characteristics which result in performance which is unsurpassed by any rectifier previously available. With basic ratings of 1200 volts and 16 amps continuous current, the HFA16PB120 is especially well suited for use as the companion diode for IGBTs and MOSFETs. In addition to ultra fast recovery time, the HEXFRED product line features extremely low values of peak recovery current ( $I_{RRM}$ ) and does not exhibit any tendency to "snap-off" during the  $t_b$  portion of recovery. The HEXFRED features combine to offer designers a rectifier with lower noise and significantly lower switching losses in both the diode and the switching transistor. These HEXFRED advantages can help to significantly reduce snubbing, component count and heatsink sizes. The HEXFRED HFA16PB120 is ideally suited for applications in power supplies and power conversion systems (such as inverters), motor drives, and many other similar applications where high speed, high efficiency is needed.

## Absolute Maximum Ratings

	Parameter	Max.	Units
$V_R$	Cathode-to-Anode Voltage	1200	V
$I_F @ T_C = 100^\circ C$	Continuous Forward Current	30	A
$I_{FSM}$	Single Pulse Forward Current	120	
$I_{FRM}$	Maximum Repetitive Forward Current	90	
$P_D @ T_C = 25^\circ C$	Maximum Power Dissipation	350	W
$P_D @ T_C = 100^\circ C$	Maximum Power Dissipation	140	
$T_J$ $T_{STG}$	Operating Junction and Storage Temperature Range	-55 to + 150	$^\circ C$

\* 125°C

Document Number: 93090

07/27/04

www.vishay.com

1

# HFA30PB120

International  
 Rectifier

## Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

Symbol	Parameter	Min.	Typ.	Max.	Units	Conditions
$V_{BR}$	Cathode Anode Breakdown Voltage	1200	—	—	V	$I_R = 100\mu\text{A}$
$V_{FM}$	Max Forward Voltage	—	2.4	4.1	V	$I_F = 30\text{A}$
		—	3.1	5.7		$I_F = 60\text{A}$ See Fig. 1
		—	2.3	4.0		$I_F = 30\text{A}, T_J = 125^\circ\text{C}$
$I_{RM}$	Max Reverse Leakage Current	—	1.3	40	$\mu\text{A}$	$V_R = V_R$ Rated See Fig. 2
		—	1.1	4000		$T_J = 125^\circ\text{C}, V_R = 0.8 \times V_R$ Rated
$C_T$	Junction Capacitance	—	50	75	pF	$V_R = 200\text{V}$ See Fig. 3
$L_S$	Series Inductance	—	8.0	—	nH	Measured lead to lead 5mm from package body

## Dynamic Recovery Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

Symbol	Parameter	Min.	Typ.	Max.	Units	Conditions
$t_{rr}$	Reverse Recovery Time	—	47	—	ns	$I_F = 1.0\text{A}, di_F/dt = 200\text{A}/\mu\text{s}, V_R = 30\text{V}$
$t_{rr1}$	See Fig. 5, 10	—	110	170		$T_J = 25^\circ\text{C}$
$t_{rr2}$		—	170	260		$T_J = 125^\circ\text{C}$
$I_{RRM1}$	Peak Recovery Current	—	10	15	A	$T_J = 25^\circ\text{C}$ $I_F = 30\text{A}$
$I_{RRM2}$	See Fig. 6	—	16	24		$T_J = 125^\circ\text{C}$
$Q_{rr1}$	Reverse Recovery Charge	—	650	980	nC	$T_J = 25^\circ\text{C}$ $V_R = 200\text{V}$
$Q_{rr2}$	See Fig. 7	—	1540	2310		$T_J = 125^\circ\text{C}$
$di_{(rec)}/dt1$	Peak Rate of Fall of Recovery Current	—	270	—	A/ $\mu\text{s}$	$T_J = 25^\circ\text{C}$ $di_F/dt = 200\text{A}/\mu\text{s}$
$di_{(rec)}/dt1$	During $t_b$ See Fig. 8	—	240	—		$T_J = 125^\circ\text{C}$

## Thermal - Mechanical Characteristics

	Parameter	Min.	Typ.	Max.	Units
$T_{lead}^{(2)}$	Lead Temperature	—	—	300	$^\circ\text{C}$
$R_{qJC}$	Thermal Resistance, Junction-to-Case	—	—	0.36	$^\circ\text{C}/\text{W}$
$R_{qJA}^{(3)}$	Thermal Resistance, Junction-to-Ambient	—	—	80	
$R_{qCS}^{(4)}$	Thermal Resistance, Case-to-Heat Sink	—	0.50	—	
$Wt$	Weight	—	2.0 (0.07)	—	g (oz.)
	Mounting Torque	6.0	—	12	kg-cm
		5.0	—	10	lbf-in

### Notes:


- ①  $L = 100\mu\text{H}$ , duty cycle limited by max  $T_J$
- ② 0.063 in. from Case (1.6mm) for 10 sec
- ③ Typical Socket Mount
- ④ Mounting Surface, Flat, Smooth and Greased

Document Number: 93090


www.vishay.com

2


# HFA30PB120




**Fig. 1 - Maximum Forward Voltage Drop vs. Instantaneous Forward Current**



**Fig. 2 - Typical Reverse Current vs. Reverse Voltage**




**Fig. 3 - Typical Junction Capacitance vs. Reverse Voltage**




**Fig. 4 - Maximum Thermal Impedance  $Z_{thjc}$  Characteristics**

# HFA30PB120


International  
**IR** Rectifier




**Fig. 5** - Typical Reverse Recovery vs.  $di_f/dt$ ,  
(per Leg)




**Fig. 6** - Typical Recovery Current vs.  $di_f/dt$ ,  
(per Leg)




**Fig. 7** - Typical Stored Charge vs.  $di_f/dt$ ,  
(per Leg)





**Fig. 8** - Typical  $di_{(rec)M}/dt$  vs.  $di_f/dt$ ,  
(per Leg)



**Fig. 9 - Reverse Recovery Parameter Test Circuit**



**Fig. 10 - Reverse Recovery Waveform and Definitions**



**Fig. 11 - Avalanche Test Circuit and Waveforms**





## Notice

The products described herein were acquired by Vishay Intertechnology, Inc., as part of its acquisition of International Rectifier's Power Control Systems (PCS) business, which closed in April 2007. Specifications of the products displayed herein are pending review by Vishay and are subject to the terms and conditions shown below.

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.

International Rectifier®, IR®, the IR logo, HEXFET®, HEXSense®, HEXDIP®, DOL®, INTERO®, and POWIRTRAIN® are registered trademarks of International Rectifier Corporation in the U.S. and other countries. All other product names noted herein may be trademarks of their respective owners.