



Contact Data

Contact form	: 2 form C.
Contact material	: Ag Alloy.
Contact rating	: Resistive: 8A 250V ac/30V dc. Inductive: 4A 250V ac Cos Ø = 0.4.
Maximum switching voltage	: 380V ac/30V dc.
Maximum switching current	: 8A.
Maximum switching power	: 2000VA, 240W.
Minimum switching load	: 5V dc, 100mA.
Maximum contact resistance	: 100mΩ (6V dc 1A).

Life

Electrical	: 100,000 operations. 50,000 operations (Inductive: Cos Ø0.4, L/R = 7ms).
Mechanical	: 20,000,000 operations.

General Data

Minimum insulation resistance	: 10,000MΩ 500V dc.
Dielectric strength	: 1000V ac, 1 min between open contacts 5000V ac, 1 min between coil and contacts.
Operate time	: Maximum 10ms.
Release time	: Maximum 5ms.
Operate temperature	: -40 to +85°C.

Shock Resistance

Endurance	: 1000m/s ² .
Misoperation	: 100m/s ² .


Vibration Resistance

Endurance	: 10 to 55Hz, 1.5mm double amplitude.
Misoperation	: 10 to 55Hz, 1.5mm double amplitude.
Humidity	: 35% to 95%RH, +40°C.


Coil Data Chart 20°C

Nominal Voltage V dc	Coil Resistance Ω ±10%	Operate Voltage ≤ V dc	Release Voltage ≥ V dc	Coil Power mW	Enclosure	Contact Form	Part Number
12	360	8.4	1.2	400	Plastic Sealed Type	2 form C	MC25129
24	1440	16.8	2.4				MC25128


Dimensions (mm)



Wiring Diagrams (Bottom View)




Mounting Hole Layout (Bottom View)




Dimensions : Millimetres

Characteristic Chart Data


Maximum DC Resistive Load Breaking Capacity



Operate Range



Life Curve



Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2011.