

Actuators for safety switches NZ.VZ, NZ.VZ.VS and TZ

- ▶ Two stainless safety screws per actuator
- ▶ Increased overtravel optional
- ▶ Packaging unit 25 pieces optional

Straight actuator

The straight actuator is used on sliding doors or hinged doors with door radii greater than 1000 mm. Safety screws prevent unscrewing of the actuator. The safety screws included can be inserted with a normal tool, but cannot be removed again.


Actuator with overtravel

- ▶ **4 mm** for doors with normal play
- ▶ **16 mm** for doors with large play (optional)

Actuator Z-G straight


Overtravel 4 mm

Dimension drawings




Actuator Z-GME straight

Overtravel 4 mm, solid stainless steel




Actuator Z-GN straight

Overtravel 16 mm



Selection table for actuators

Actuator					
Actuator straight Z-G 016 849 overtravel 4 mm					
Actuator straight Z-GME 097 436 overtravel 4 mm					
Actuator straight Z-GN 072 251 overtravel 16 mm					



Ordering table

Designation	Version	Min. door radius r [mm]	Packaging unit	Order No.
Actuator straight	Z-G 4 mm overtravel incl. 2 safety screws M5 x 10	≥ 1000	1 ea.	016 849 ACTUATOR-Z-G
			25 ea.	074 411 ACTUATOR-Z-G/V25
	Z-GME 4 mm overtravel, made of solid stainless steel incl. 2 safety screws M5x10	≥ 1000	1 ea.	097 436 ACTUATOR-Z-GME
	Z-GN 16 mm overtravel incl. 2 safety screws M5x10	≥ 1000	1 ea.	072 251 ACTUATOR-Z-GN

For safety precautions see page 179
 For technical data see page 151