



List Price \$287.00 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.****Technical Characteristics**

Contact Configuration	1 N.O./1 N.C.
Contact Operation	Snap Action
Contact Form	Form Z - SPDT-DB
Terminal Type	Screw Clamp
Ampere Rating	15A
Maximum Voltage Rating	600V
Enclosure Rating	NEMA 1/2/4/12/13
Head Type	Rotary
Mounting Type	Front/Rear
Operating Temperature Range	-65 to 185 Degrees F
Type	AW
Type of Duty	Heavy Duty
Actuation	CCW
Actuator Action	Momentary
Actuator	Lever Arm (ordered separately)
Operating Torque/Force	2.75 Inch-Pounds
Total Travel	30 Degrees
Differential Travel	2.5 Degrees
Pre-Travel	5 Degrees
Approvals	UL Listed File Number E42259 CCN NKCR - CSA Certified File Number LR25490 Class 3211-03 - CE Marked
Body Type	Standard Box
Body Material	Cast Zinc
Connection Type	Conduit Entrance (0.5 Inch NPT)

**Shipping and Ordering**

Category	21496 - Limit Switches, Heavy Duty, Precision, Type AW
Discount Schedule	CP1
GTIN	00785901807629
Package Quantity	10
Weight	1.05 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y

Generated: 06/16/2011 02:50:06

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.