

Miniature Fuse, 5 x 20 mm



IEC 60127-2 · 250 VAC · Time-Lag T

**Description**

- IEC Standard Fuse
- H = High Breaking Capacity (Ceramic Tube)

Standards

- IEC 60127-2/5
- UL 248-14
- CSA C22.2 no. 248.14

Approvals

- VDE License Number: 139234 (1 A - 6.3 A), 40014395 (8 A - 16 A)
- UL File Number: E41599

Applications

- Primary Protection in Equipment
- Power Supply Adapter for e.g. laptops
- SMPS (Switching Mode Power Supply) for TV's and DVD's

References

General Product Information

Time-Current Curves see last page

Pigtail Type [SPT 5x20 Pigtail](#)


Fuse Kit [Miniature Fuses 5x20](#)

Weblinks

Approvals: <http://www.schurter.com/approvals>


RoHS: <http://www.schurter.com/rohs>

Technical Data

Rated Voltage	250 VAC
Rated Current	0.5 - 16 A
Breaking Capacity	500 A - 1500 A
Characteristic	Time-Lag T
Admissible Ambient Air Temp.	-55 °C to 125 °C
Climatic Category	55/125/21 acc. to IEC 60068-1
Material: Tube	Ceramic
Material: Endcaps	Nickel-Plated Copper Alloy
Unit Weight	1.16 g
Storage Conditions	0 °C to 60 °C, max. 70% r.h.
Product Marking	 Current Rating, Voltage Rating, Characteristic, Breaking Capacity, Approvals

Dimensions







Length  20 mm



Pre-Arcing Time

Rated Current In	1.5 x In min.	2.1 x In max.	2.75 x In min.	2.75 x In max.	4.0 x In min.	4.0 x In max.	10.0 x In min.	10.0 x In max.
0.5 A - 0.8 A	60 min	30 min	250 ms	80 s	50 ms	5 s	5 ms	150 ms
1 A - 3.15 A	60 min	30 min	750 ms	80 s	95 ms	5 s	10 ms	150 ms
4 A - 6.3 A	60 min	30 min	750 ms	80 s	150 ms	5 s	10 ms	150 ms
8 A - 10 A	30 min	30 min	750 ms	80 s	150 ms	5 s	10 ms	150 ms
12.5 A - 16 A	15 min	30 min	750 ms	80 s	150 ms	5 s	20 ms	150 ms

Variants

Order Number	Rated Current [A]	Rated Voltage [VAC]	Breaking Capacity	Voltage Drop 1.0 In max [mV]	Voltage Drop 1.0 In typ [mV]	Power Dissipation 1.5 In max [mW]	Power Dissipation 1.5 In typ [mW]	Melting I ² t 10.0 In typ [A ² s]						
0001.2501	0.5	250	1)	850	360	1600	500	0.5			●			
0001.2502	0.63	250	1)	650	330	1600	500	1.55			●			
0001.2503	0.8	250	1)	500	260	1600	500	2.3			●			
0001.2504	1	250	1)	350	180	2500	500	1.1	●		●	●	●	●
0001.2505	1.25	250	1)	300	150	2500	500	1.86	●		●	●	●	●
0001.2506	1.6	250	1)	200	130	2500	500	4.35	●		●	●	●	●
0001.2507	2	250	1)	190	120	2500	600	9.2	●		●	●	●	●
0001.2508	2.5	250	1)	180	100	2500	600	11.7	●		●	●	●	●
0001.2509	3.15	250	1)	140	100	4000	800	33.7	●		●	●	●	●
0001.2510	4	250	1)	100	90	4000	900	62.4	●		●	●	●	●
0001.2511	5	250	1)	100	90	4000	1200	97.5	●		●	●	●	●
0001.2512	6.3	250	1)	100	70	4000	1200	171	●		●	●	●	●
0001.2513	8	250	2)	100	70	4000	1300	268		●	●	●		●
0001.2514	10	250	2)	100	70	4000	2100	400		●	●	●		
0001.2515	12.5	250	3)		70		3100	563		●	●	●		
0001.2516	16	250	3)		70		4000	1500		●	●			

1) IEC: H = 1500 A @ 250 VAC, p.f. = 0.7 - 0.8

1) UL: 10 kA @ 125 VAC, p.f. = 0.7 - 0.8 / 1500 A @ 250 VAC, p.f. = 0.7 - 0.8

2) IEC + UL: 1000 A @ 250 VAC

3) IEC: 500 A @ 250 VAC

3) UL: 500 A @ 125 VAC, p.f. = 0.7 - 0.8 / 1000 A @ 125 VAC / 500 A @ 250 VAC

Packaging Unit

Small Box Pack (10 pcs.)

xxxx.xxxx.G Bulk 128 x 91 x 60 mm (1000 pcs.)

SPT 5x20

