





naa

### **RoHS** Compliant



# ExpressCard LPT + 1xRS232

### "SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"

XC-475



#### Features

- 2 port 1xRS232 + 1xLPT
- ExpressCard PCIe Implementation
- 256Byte Tx and 256Byte Rx FIFOs
- Up to 921,600 Baud
- DB9 Connector (9 Pin Male) & DB25 Connector (25 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

#### Options



XC-475: ExpressCard LPT + . 1xRS232

#### Description

ExpressCard providing one RS232 serial port and one Printer port. Up to 921,600 data transfer rates and the 256 byte deep transmit and 256 byte receive FIFOS, coupled with 1Mbit/s line drivers deliver uncompromising performance on your laptop. Drivers for Windows 32 bit and 64 bit Operating Systems including Windows XP, Server 2003, Vista, Server 2008 and Windows 7.

This high performance range utilising PCIe native drivers. Excellent method of adding extra serial ports to your laptop.

With Brainboxes industry renowned Lifetime Warranty and Lifetime Support!

#### Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows 7 32 bit & 64 bit Editions
- Windows Vista 32 bit & 64 bit editions
- Windows XP 32 bit & 64 bit editions

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.



Description ExpressCard LPT + 1xRS232 Code XC-475

+44(0) 151 220 2500 | sales@brainboxes.com www.brainboxes.com Downloade

## XC-475

# ExpressCard LPT + 1xRS232

#### XC-475: Full Specification

Port	Ports	2 x - 1xRS232 + 1xLPT
Pin 1 DCD   RS232 Pinout (9 Pin Male)	Connector	DB9 Connector (9 Pin Male) & DB25 Connector (25 Pin Male)
Pin 1 DCD RS232 Pinout (9 Pin Male)   Pin 2 RXD Pin 1 Pin 5   Pin 3 TXD I I	FIFO size	256 RX FIFO + 256 TX FIFO
Pin 4 DTR Pin 5 GND	Operating Distance	EIA - RS232 Standard
Pin 6 DSR   Pin 7 RTS   Pin 8 CTS   Pin 9 RT	Cable	1xDB9 & 1xDB25
Port Settings	Baud Rate	921,600
	Data Bits	5,6,7 or 8
921,600	Parity	Odd, Even, None, Mark or Space
>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>	Stop Bits	1 or 2
baud	Flow Control	
	Tx/Rx Modes	Point to Point
Interface	OS Compatibility	Microsoft Windows 7 32 bit & 64 bit Editions
		Windows Vista 32 bit & 64 bit Editions Windows XP 32 bit & 64 bit Editions
PCI		
	BUS	ExpressCard PCIe Implementation
Approvals	Other Approvals	Microsoft Certified Gold Partner WEEE RoHS EMC: CE
	Microsoft Approvals	Microsoft Certified Gold Partner
A A A A A A A A A A A A A A A A A		Windows 7 32 bit & 64 bit Editions
Windows*7 Vista* Windows*RP		Windows Vista 32 bit & 64 bit editions
		Windows XP 32 bit & 64 bit editions
General	PCB Layers	4
	Power Consumption	380mA @ 3.3V
	Weight	0.03 kg Kg
	Size	100(l) x 35(w) x 10(h) mm mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	ExpressCard LPT + 1xRS232
	\A/arranty	1xDB9 & 1xDB25
Product Support	Warranty	Lifetime (online registration required)
	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly staff who work in and alongside the Product Development Team
Additional	OEM option	Available for bulk buy OEM
	Made In	Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"
	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More Info: sales@brainboxes.com

Made in the UK

Other Brainboxes Ranges: PCI Express | Bluetooth Serial Adapter | Ethernet to Serial Adapter | PCMCIA Serial Card | ExpressCard Serial Adapter | USB to Serial

+44(0) 151 220 2500 sales@brainboxes.com www.brainboxes.com