



THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH

| CHARACTERISTICS                | ELECTRICAL DATA                | THIRD ANGLE PROJECTION                    |
|--------------------------------|--------------------------------|---|
| OPERATING FORCE ..... 1 OZ MAX | CONTACT ARRANGEMENT<br>S P D T | SCALE FULL                                |
|                                | L156                           | DO NOT SCALE PRINT                        |
|                                | 11A 1/3HP 125, 250, 277 VAC    | UNLESS OTHERWISE SPECIFIED TOLERANCES ARE |
|                                | 1/2A 125 VDC, 1/4A 250 VDC     | ONE PLACE (.01) ±.030                     |
|                                | 4A 125 VAC "L"                 | TWO PLACE (.00) ±.015                     |
|                                |                                | THREE PLACE (.000) ±.005                  |
|                                |                                | ANGLES ±                                  |
|                                |                                | WEIGHT                                    |

ANSI Y14.5M-1982 APPLIES

MICROSWITCH a Honeywell Division  
 CATALOG LISTING  
 BFL1-BW4  
 SWITCH - ENCLOSED  
 CATALOG LISTING  
 BFL1-BW4  
 RELEASE NO. 203802  
 REPLACES 22AUG00  
 ISSUE 1  
 OF 1  
 CHECK  
 REVISIONS  
 CHECK  
 7SEP01  
 CHECK  
 SAV  
 CHECK  
 7SEP01  
 CHECK  
 KED  
 PTC/CAD 20  
 DRAWN