


7mm 85°C MCMR Series



Features:

- Developed short body length to 7mm, for the demand of smaller and thinner electronic equipment.
- Most suitable for high-density electronic equipment, such as: automatic office machines, pocket calculators, car stereos and mini-audio sets, VCR, camera, CD-ROM, notebook, etc.


Specifications:

Item	Performance																								
Operating temperature range	-40 to +85°C																								
Rated working voltage range	6.3 to 63V dc																								
Nominal capacitance range	0.1 to 470µF																								
Capacitance tolerance	±20% (at +20°C, 120Hz)																								
Leakage current	I = 0.01CV or 3(µA) after two minutes																								
Dissipation factor (tan δ) (120Hz/+20°C)	<table border="1"> <tr> <td>Working voltage (V)</td> <td>6.3</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> <td>63</td> </tr> <tr> <td>Maximum tan δ</td> <td>0.24</td> <td>0.20</td> <td>0.16</td> <td>0.14</td> <td>0.12</td> <td>0.10</td> <td>0.08</td> </tr> </table>	Working voltage (V)	6.3	10	16	25	35	50	63	Maximum tan δ	0.24	0.20	0.16	0.14	0.12	0.10	0.08								
	Working voltage (V)	6.3	10	16	25	35	50	63																	
Maximum tan δ	0.24	0.20	0.16	0.14	0.12	0.10	0.08																		
Characteristics at high and low temperature (stability at 120Hz)	<table border="1"> <tr> <td>Working voltage (V)</td> <td>6.3</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> <td>63</td> </tr> <tr> <td>-25°C/+20°C</td> <td>4</td> <td>3</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> </tr> <tr> <td>-40°C/+20°C</td> <td>8</td> <td>6</td> <td>4</td> <td>4</td> <td>3</td> <td>3</td> <td>3</td> </tr> </table>	Working voltage (V)	6.3	10	16	25	35	50	63	-25°C/+20°C	4	3	2	2	2	2	2	-40°C/+20°C	8	6	4	4	3	3	3
	Working voltage (V)	6.3	10	16	25	35	50	63																	
	-25°C/+20°C	4	3	2	2	2	2	2																	
-40°C/+20°C	8	6	4	4	3	3	3																		
High temperature loading	<p>After 1000 hours application of DC rated working voltage at +85°C, The capacitor shall meet the following limits : Post test requirements at +20°C.</p> <table border="1"> <tr> <td>Leakage current</td> <td>£ the initial specified value</td> </tr> <tr> <td>Capacitance change</td> <td>£ ±20% of initial measured value</td> </tr> <tr> <td>Dissipation factor (tan δ)</td> <td>£ 200% of initial specified value</td> </tr> </table>	Leakage current	£ the initial specified value	Capacitance change	£ ±20% of initial measured value	Dissipation factor (tan δ)	£ 200% of initial specified value																		
	Leakage current	£ the initial specified value																							
	Capacitance change	£ ±20% of initial measured value																							
Dissipation factor (tan δ)	£ 200% of initial specified value																								
Shelf life	<p>After storage for 500 hours at +85°C with no voltage applied. Post test requirements at +20°C same limits as high temperature loading.</p>																								
Solvent proof	<p>This capacitor can withstand circuit-board cleaning within 5 min. dipped in Freon TE, TES at 40°C (ultrasonic also permitted) or in the steam of these cleaners.</p>																								

7mm 85°C MCMR Series



Diagram of Dimensions



Dimensions : Millimetres

$\text{Ø}D$ (+0.5 Maximum)	3	4	5	6.3	8
F (± 0.5)	1.0	1.5	2	2.5	3.5
$\text{Ø}d$ (± 0.02)	0.4	0.45	0.45	0.45	0.5

Case Size Table $\text{Ø}D \times L$ (mm)

μF \ W.V. (SV)	6.3	10	16	25	35	50	63	
	(8)	(13)	(20)	(32)	(44)	(63)	(79)	
0.1	-	-	-	-	R	4 x 7	4 x 7	
0.22	-	-	-	-				
0.33	-	-	-	-				
0.47	-	-	-	-				
1.0	-	-	-	-				
2.2	-	-	-	-				
3.3	-	-	-	-				
4.7	-	-	-	-				
10	-	-	R	4 x 7	4 x 7	5 x 7	6.3 x 7	
22	-	R	4 x 7	5 x 7	5 x 7	6.3 x 7	-	
33	R	4 x 7	5 x 7	6.3 x 7	6.3 x 7	8 x 7 (8 x 9)	-	
47				6.3 x 7			-	
100		5 x 7	6.3 x 7	8 x 7 (8 x 9)	8 x 7 (8 x 9)	-	-	
220		6.3 x 7	8 x 7 (8 x 9)	-	-	-	-	
330		8 x 7 (8 x 9)		-	-	-	-	
470		8 x 7 (8 x 9)	8 x 9	8 x 9	-	-	-	-

All blank voltage on sleeve marking is the same voltage as "R" point to.



7mm 85°C MCMR Series



Part Number Table

Description	Part Number
CAPACITOR, 33UF, 10V	MCMR10V336M4X7
CAPACITOR, 47UF, 10V	MCMR10V476M4X7
CAPACITOR, 100UF, 10V	MCMR10V107M5X7
CAPACITOR, 220UF, 10V	MCMR10V227M6.3X7
CAPACITOR, 330UF, 10V	MCMR10V337M8X7
CAPACITOR, 470UF, 10V	MCMR10V477M8X9
CAPACITOR, 22UF, 16V	MCMR16V226M4X7
CAPACITOR, 33UF, 16V	MCMR16V336M5X7
CAPACITOR, 47UF, 16V	MCMR16V476M5X7
CAPACITOR, 100UF, 16V	MCMR16V107M6.3X7
CAPACITOR, 220UF, 16V	MCMR16V227M8X7
CAPACITOR, 330UF, 16V	MCMR16V337M8X7
CAPACITOR, 470UF, 16V	MCMR16V477M8X9
CAPACITOR, 10UF, 25V	MCMR25V106M4X7
CAPACITOR, 22UF, 25V	MCMR25V226M5X7
CAPACITOR, 33UF, 25V	MCMR25V336M5X7
CAPACITOR, 47UF, 25V	MCMR25V476M6.3X7
CAPACITOR, 100UF, 25V	MCMR25V107M8X7
CAPACITOR, 10UF, 35V	MCMR35V106M4X7
CAPACITOR, 22UF, 35V	MCMR35V226M5X7
CAPACITOR, 33UF, 35V	MCMR35V336M6.3X7
CAPACITOR, 47UF, 35V	MCMR35V476M6.3X7
CAPACITOR, 100UF, 35V	MCMR35V107M8X7
CAPACITOR, 0.1uF, 50V	MCMR50V104M4X7
CAPACITOR, 0.22uF, 50V	MCMR50V224M4X7
CAPACITOR, 0.33uF, 50V	MCMR50V334M4X7
CAPACITOR, 0.47uF, 50V	MCMR50V474M4X7
CAPACITOR, 1uF, 50V	MCMR50V105M4X7
CAPACITOR, 2.2uF, 50V	MCMR50V225M4X7
CAPACITOR, 3.3uF, 50V	MCMR50V335M4X7

CAPACITOR, 4.7uF, 50V	MCMR50V475M4X7
CAPACITOR, 10uF, 50V	MCMR50V106M5X7
CAPACITOR, 22uF, 50V	MCMR50V226M5X7
CAPACITOR, 33uF, 50V	MCMR50V336M8X7
CAPACITOR, 47uF, 50V	MCMR50V476M8X7
CAPACITOR, 0.1UF, 63V	MCMR63V104M4X7
CAPACITOR, 0.22UF, 63V	MCMR63V224M4X7
CAPACITOR, 0.33UF, 63V	MCMR63V334M4X7
CAPACITOR, 0.47UF, 63V	MCMR63V474M4X7
CAPACITOR, 1UF, 63V	MCMR63V105M4X7
CAPACITOR, 2.2UF, 63V	MCMR63V225M4X7
CAPACITOR, 3.3UF, 63V	MCMR63V335M4X7
CAPACITOR, 4.7UF, 63V	MCMR63V475M5X7
CAPACITOR, 10UF, 63V	MCMR63V106M6.3X7

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC Multicomp is the registered trademark of the Group. © Premier Farnell plc 2011.

<http://www.farnell.com>
<http://www.newark.com>
<http://www.cpc.co.uk>

