

## Polypropylene (PP) Capacitors for Pulse Applications with Double-Sided Metallized Electrodes and Schoopage Contacts PCM 7.5 mm to 37.5 mm

### Special Features

- Pulse duty construction
- Self-healing
- Very low dissipation factor
- Negative capacitance change versus temperature
- According to RoHS 2002/95/EC

### Typical Applications

- For pulse applications e.g.
- Switch mode power supplies
  - TV and monitor sets
  - Lighting
  - Audio/video equipment


### Construction

**Dielectric:** Polypropylene (PP) film

**Capacitor electrodes:**

Double-sided metallized plastic film

**Internal construction:**



### Encapsulation:

Solvent-resistant, flame-retardant plastic case with epoxy resin seal, UL 94 V-0

**Terminations:** Tinned wire.

**Marking:** Colour: Red.

Marking: Black. Epoxy resin seal: Red

### Electrical Data

#### Capacitance range:

1000 pF to 15  $\mu$ F (E12-values on request)

#### Rated voltages:

100 VDC, 250 VDC, 400 VDC, 630 VDC, 1000 VDC, 1600 VDC, 2000 VDC, 2500 VDC

#### Capacitance tolerances:

$\pm 20\%$ ,  $\pm 10\%$ ,  $\pm 5\%$

#### Operating temperature range:

$-55^{\circ}$  C to  $+100^{\circ}$  C

#### Climatic test category:

55/100/56 in accordance with IEC

#### Insulation resistance at $+20^{\circ}$ C:

$C \leq 0.33 \mu\text{F}$ :  $\geq 1 \times 10^5 \text{ M}\Omega$

(mean value:  $5 \times 10^5 \text{ M}\Omega$ )

$C > 0.33 \mu\text{F}$ :  $\geq 30000 \text{ sec (M}\Omega \times \mu\text{F)}$

(mean value: 100000 sec)

Measuring voltage: 100 V/1 min.

#### Dissipation factors at $+20^{\circ}$ C: $\tan \delta$

at f	$C \leq 0.1 \mu\text{F}$	$0.1 \mu\text{F} < C \leq 1.0 \mu\text{F}$	$C > 1.0 \mu\text{F}$
1 kHz	$\leq 3 \times 10^{-4}$	$\leq 3 \times 10^{-4}$	$\leq 3 \times 10^{-4}$
10 kHz	$\leq 4 \times 10^{-4}$	$\leq 6 \times 10^{-4}$	-
100 kHz	$\leq 15 \times 10^{-4}$	-	-

**Test voltage:**  $1.6 U_r$ , 2 sec.

#### Dielectric absorption:

0.05%

#### Voltage derating:

A voltage derating factor of 1.35 % per K must be applied from  $+85^{\circ}$  C for DC voltages and from  $+75^{\circ}$  C for AC voltages.

#### Reliability:

Operational life  $> 300000$  hours

Failure rate  $< 1$  fit ( $0.5 \times U_r$  and  $40^{\circ}$  C)

### Maximum pulse rise time:

Capacitance $\mu\text{F}/\mu\text{F}$	max. pulse rise time V/ $\mu\text{sec}$ at $T_A < 40^{\circ}$ C							
	100 VDC	250 VDC	400 VDC	630 VDC	1000 VDC	1600 VDC	2000 VDC	2500 VDC
1000 ... 2200	1000	1800	1800	1800	2800	5400	9000	11000
3300 ... 6800	900	1200	1200	1200	2800	5400	9000	11000
0.01 ... 0.022	700	1100	1200	1800	2100	3000	3400	11000
0.033 ... 0.068	400	800	900	1800	2100	2100	2100	-
0.1 ... 0.22	200	500	500	900	1400	1400	1400	-
0.33 ... 0.68	100	300	400	700	900	900	900	-
1.0 ... 2.2	70	200	200	400	400	500	-	-
3.3 ... 4.7	50	80	100	150	-	-	-	-
6.8 ... 15	35	50	70	-	-	-	-	-

for pulses equal to the rated voltage

### Mechanical Tests

#### Pull test on leads:

$d \leq 0.8 \phi$ : 10 N in direction of leads

$d > 0.8 \phi$ : 20 N in direction of leads

according to IEC 60068-2-21

#### Vibration:

6 hours at 10...2000 Hz and 0.75 mm

displacement amplitude or 10 g in

accordance with IEC 60068-2-6

#### Low air density:

1kPa = 10 mbar in accordance with

IEC 60068-2-13

#### Bump test:

4000 bumps at 390 m/sec<sup>2</sup>

in accordance with IEC 60068-2-29

### Packing

Available taped and reeled up to and

including case size 15 x 26 x 31.5 /

PCM 27.5 mm.

Detailed taping information and graphs

at the end of the catalogue.

For further details and graphs please

refer to Technical Information.

## Continuation

### General Data

Capacitance	100 VDC/63 VAC*					250 VDC/180 VAC*				
	W	H	L	PCM**	Part number	W	H	L	PCM**	Part number
1000 pF	4	9	10	7.5	MKP1D011002C00	4	9	10	7.5	MKP1F011002C00
1500 "	4	9	10	7.5	MKP1D011502C00	4	9	10	7.5	MKP1F011502C00
2200 "	4	9	10	7.5	MKP1D012202C00	4	9	10	7.5	MKP1F012202C00
3300 "	4	9	10	7.5	MKP1D013302C00	4	9	10	7.5	MKP1F013302C00
4700 "	4	9	10	7.5	MKP1D014702C00	4	9	10	7.5	MKP1F014702C00
6800 "	4	9	10	7.5	MKP1D016802C00	4	9	10	7.5	MKP1F016802C00
0.01 µF	4	9	10	7.5	MKP1D021002C00	4	9	10	7.5	MKP1F021002C00
0.015 "	4	9	10	7.5	MKP1D021502C00	4	9	10	7.5	MKP1F021502C00
0.022 "	4	9	10	7.5	MKP1D022202C00	4	9	10	7.5	MKP1F022202C00
0.033 "	5	10.5	10.3	7.5	MKP1D023302E00	5	10.5	10.3	7.5	MKP1F023302E00
0.047 "	5	10.5	10.3	7.5	MKP1D024702E00	5	10.5	10.3	7.5	MKP1F024702E00
0.068 "	5	11	13	10	MKP1D026803F00	5	11	13	10	MKP1F026803F00
0.1 µF	6	12	13	10	MKP1D031003G00	6	12	13	10	MKP1F031003G00
0.15 "	6	12.5	18	15	MKP1D031504C00	6	12.5	18	15	MKP1F031504C00
0.22 "	7	14	18	15	MKP1D032204D00	7	14	18	15	MKP1F032204D00
0.33 "	8	15	18	15	MKP1D033304F00	8	15	18	15	MKP1F033304F00
0.47 "	9	16	18	15	MKP1D034704J00	9	16	18	15	MKP1F034704J00
0.68 "	8.5	18.5	26.5	22.5	MKP1D036805F00	8.5	18.5	26.5	22.5	MKP1F036805F00
1.0 µF	10.5	19	26.5	22.5	MKP1D041005G00	11	21	26.5	22.5	MKP1F041005I00
1.5 "	11	21	31.5	27.5	MKP1D041506B00	11	21	31.5	27.5	MKP1F041006B00
2.2 "	13	24	31.5	27.5	MKP1D042206D00	13	24	31.5	27.5	MKP1F041506D00
3.3 "	17	29	31.5	27.5	MKP1D043306G00	13	24	41.5	37.5	MKP1F041507C00
4.7 "	20	39.5	31.5	27.5	MKP1D044706J00	15	26	31.5	27.5	MKP1F042206F00
6.8 "	17	29	41.5	37.5	MKP1D044707E00	13	24	41.5	37.5	MKP1F042207C00
10 µF	19	32	41.5	37.5	MKP1D046807F00	17	34.5	31.5	27.5	MKP1F043306I00
15 "	20	39.5	41.5	37.5	MKP1D051007G00	17	29	41.5	37.5	MKP1F043307E00
	24	45.5	41.5	37.5	MKP1D051507H00	20	39.5	31.5	27.5	MKP1F044706J00
						19	32	41.5	37.5	MKP1F044707F00
						20	39.5	41.5	37.5	MKP1F046807G00


\* AC voltage:  $f \leq 1000 \text{ Hz}$ ;  $1.4 \times U_{\text{rms}} + U_{\text{DC}} \leq U_r$

\*\* PCM = Printed circuit module = lead spacing

Dims. in mm.

Ionisation inception level in isolated cases may be lower than admissible AC voltage.

ø d	PCM
0.6	7.5 - 10
0.8	15 - 27.5
1.0	37.5



Part number completion:

Tolerance: 20 % = M  
10 % = K  
5 % = J

Packing: bulk = S  
Lead length: 6-2 = SD

Taped version see page 127.

Rights reserved to amend design data without prior notification.

Continuation page 58

## Continuation

### General Data

Capacitance	400 VDC/250 VAC*					630 VDC/400 VAC*				
	W	H	L	PCM**	Part number	W	H	L	PCM**	Part number
1000 pF	4	9	10	7.5	MKP1G011002C00	4	9	10	7.5*	MKP1J011002C00
1500 "	4	9	10	7.5	MKP1G011502C00	4	9	10	7.5*	MKP1J011502C00
2200 "	4	9	10	7.5	MKP1G012202C00	4	9	10	7.5*	MKP1J012202C00
3300 "	4	9	10	7.5	MKP1G013302C00	4	9	10	7.5*	MKP1J013302C00
4700 "	4	9	10	7.5	MKP1G014702C00	4	9	10	7.5*	MKP1J014702C00
6800 "	4	9	10	7.5	MKP1G016802C00	4	9	10	7.5*	MKP1J016802C00
						4	9	13	10	MKP1J016803C00
0.01 µF	4	9	10	7.5	MKP1G021002C00	5	10.5	10.3	7.5*	MKP1J021002E00
	4	9	13	10	MKP1G021003C00	4	9	13	10	MKP1J021003C00
0.015 "	5	10.5	10.3	7.5	MKP1G021502E00	5	11	13	10	MKP1J021503F00
	4	9	13	10	MKP1G021503C00	5	11	18	15	MKP1J021504B00
0.022 "	5	10.5	10.3	7.5	MKP1G022202E00	5	11	13	10	MKP1J022203F00
	4	9	13	10	MKP1G022203C00	5	11	18	15	MKP1J022204B00
0.033 "	5.7	12.5	10.3	7.5	MKP1G023302F00	6	12	13	10	MKP1J023303G00
	5	11	13	10	MKP1G023303F00	5	11	18	15	MKP1J023304B00
0.047 "	6	12	13	10	MKP1G024703G00	6	12.5	18	15	MKP1J024704C00
	5	11	18	15	MKP1G024704B00	6	15	26.5	22.5	MKP1J024705B00
0.068 "	6	12.5	18	15	MKP1G026804C00	7	14	18	15	MKP1J026804D00
	6	15	26.5	22.5	MKP1G026805B00	6	15	26.5	22.5	MKP1J026805B00
0.1 µF	7	14	18	15	MKP1G031004D00	9	16	18	15	MKP1J031004J00
	6	15	26.5	22.5	MKP1G031005B00	7	16.5	26.5	22.5	MKP1J031005D00
0.15 "	8	15	18	15	MKP1G031504F00	8.5	18.5	26.5	22.5	MKP1J031505F00
	6	15	26.5	22.5	MKP1G031505B00	9	19	31.5	27.5	MKP1J031506A00
0.22 "	9	16	18	15	MKP1G032204J00	8.5	18.5	26.5	22.5	MKP1J032205F00
	7	16.5	26.5	22.5	MKP1G032205D00	9	19	31.5	27.5	MKP1J032206A00
0.33 "	8.5	18.5	26.5	22.5	MKP1G033305F00	11	21	26.5	22.5	MKP1J033305I00
	9	19	31.5	27.5	MKP1G033306A00	11	21	31.5	27.5	MKP1J033306B00
0.47 "	10.5	19	26.5	22.5	MKP1G034705G00	11	21	31.5	27.5	MKP1J034706B00
	9	19	31.5	27.5	MKP1G034706A00					
0.68 "	11	21	26.5	22.5	MKP1G036805I00	15	26	31.5	27.5	MKP1J036806F00
	11	21	31.5	27.5	MKP1G036806B00	13	24	41.5	37.5	MKP1J036807C00
1.0 µF	13	24	31.5	27.5	MKP1G041006D00	17	29	31.5	27.5	MKP1J041006G00
	13	24	41.5	37.5	MKP1G041007C00	15	26	41.5	37.5	MKP1J041007D00
1.5 "	17	29	31.5	27.5	MKP1G041506G00	20	39.5	31.5	27.5	MKP1J041506J00
	13	24	41.5	37.5	MKP1G041507C00	19	32	41.5	37.5	MKP1J041507F00
2.2 "	20	39.5	31.5	27.5	MKP1G042206J00	20	39.5	41.5	37.5	MKP1J042207G00
	17	29	41.5	37.5	MKP1G042207E00					
3.3 "	20	39.5	41.5	37.5	MKP1G043307G00	24	45.5	41.5	37.5	MKP1J033307H00
4.7 "	20	39.5	41.5	37.5	MKP1G044707G00					
6.8 "	24	45.5	41.5	37.5	MKP1G046807H00					

\* AC voltage:  $f \leq 1000 \text{ Hz}$ ;  $1.4 \times U_{\text{rms}} + \text{UDC} \leq U_r$

\*\* PCM = Printed circuit module = lead spacing

\* Admissible AC voltage 280 VAC max.

Dims. in mm.

Ionisation inception level in isolated cases may be lower than admissible AC voltage.

Part number completion:

Tolerance: 20 % = M  
10 % = K  
5 % = J

Packing: bulk = S  
Lead length: 6-2 = SD

Taped version see page 127.

Rights reserved to amend design data without prior notification.

Continuation page 59



## Continuation

### General Data

Capacitance	1000 VDC/600 VAC*					1600 VDC/650 VAC*				
	W	H	L	PCM**	Part number	W	H	L	PCM**	Part number
1000 pF	4	9	10	<b>7.5</b>	MKP1O111002C00_____	4	9	13	10	MKP1T011003C00_____
	4	9	13	10	MKP1O111003C00_____					
1500 "	4	9	10	<b>7.5</b>	MKP1O111502C00_____	4	9	13	10	MKP1T011503C00_____
	4	9	13	10	MKP1O111503C00_____					
2200 "	4	9	10	<b>7.5</b>	MKP1O112202C00_____	4	9	13	10	MKP1T012203C00_____
	4	9	13	10	MKP1O112203C00_____					
3300 "	4	9	10	<b>7.5</b>	MKP1O113302C00_____	4	9	13	10	MKP1T013303C00_____
	4	9	13	10	MKP1O113303C00_____					
4700 "	4.5	9.5	10.3	<b>7.5</b>	MKP1O114702D00_____	5	11	13	10	MKP1T014703F00_____
	4	9	13	10	MKP1O114703C00_____					
6800 "	5.7	12.5	10.3	<b>7.5</b>	MKP1O116802F00_____	6	12	13	10	MKP1T016803G00_____
	5	11	13	10	MKP1O116803F00_____					
0.01 µF	5	11	13	10	MKP1O121003F00_____	5	11	18	15	MKP1T021004B00_____
	5	11	18	15	MKP1O121004B00_____					
0.015 "	6	12	13	10	MKP1O121503G00_____	6	12.5	18	15	MKP1T021504C00_____
	5	11	18	15	MKP1O121504B00_____					
0.022 "	6	12.5	18	15	MKP1O122204C00_____	7	14	18	15	MKP1T022204D00_____
	6	15	26.5	22.5	MKP1O122205B00_____					
0.033 "	7	14	18	15	MKP1O123304D00_____	8	15	18	15	MKP1T023304F00_____
	6	15	26.5	22.5	MKP1O123305B00_____					
0.047 "	8	15	18	15	MKP1O124704F00_____	7	16.5	26.5	22.5	MKP1T024705D00_____
	6	15	26.5	22.5	MKP1O124705B00_____					
0.068 "	7	16.5	26.5	22.5	MKP1O126805D00_____	10.5	19	26.5	22.5	MKP1T026805G00_____
0.1 µF	8.5	18.5	26.5	22.5	MKP1O131005F00_____	11	21	26.5	22.5	MKP1T031005I00_____
	11	21	31.5	27.5	MKP1O131006B00_____					
0.15 "	11	21	26.5	22.5	MKP1O131505I00_____	13	24	31.5	27.5	MKP1T031506D00_____
	11	21	31.5	27.5	MKP1O131506B00_____					
0.22 "	11	21	31.5	27.5	MKP1O132206B00_____	15	26	31.5	27.5	MKP1T032206F00_____
0.33 "	15	26	31.5	27.5	MKP1O133306F00_____	17	34.5	31.5	27.5	MKP1T033306I00_____
	13	24	41.5	37.5	MKP1O133307C00_____					
0.47 "	17	29	31.5	27.5	MKP1O134706G00_____	20	39.5	31.5	27.5	MKP1T034706J00_____
	13	24	41.5	37.5	MKP1O134707C00_____					
0.68 "	20	39.5	31.5	27.5	MKP1O136806J00_____	20	39.5	41.5	37.5	MKP1T036807G00_____
	17	29	41.5	37.5	MKP1O136807E00_____					
1.0 µF	20	39.5	41.5	37.5	MKP1O141007G00_____	24	45.5	41.5	37.5	MKP1T041007H00_____
1.5 "	24	45.5	41.5	37.5	MKP1O141507H00_____					

\* AC voltage:  $f \leq 1000 \text{ Hz}$ ;  $1.4 \times U_{\text{rms}} + U_{\text{DC}} \leq U_r$

\*\* PCM = Printed circuit module = lead spacing

Dims. in mm.

Ionisation inception level in isolated cases may be lower than admissible rated AC voltage.

Part number completion:

Tolerance: 20 % = M  
10 % = K  
5 % = J

Packing: bulk = S  
Lead length: 6-2 = SD

Taped version see page 127.

Rights reserved to amend design data without prior notification.

Continuation page 60



## Continuation

### General Data

Capacitance	2000 VDC/700 VAC*					2500 VDC/900 VAC*				
	W	H	L	PCM**	Part number	W	H	L	PCM**	Part number
1000 pF	4	9	13	10	MKP1U011003C00_	5	11	18	15	MKP1V011004B00_
1500 "	4	9	13	10	MKP1U011503C00_	5	11	18	15	MKP1V011005B00_
2200 "	5	11	13	10	MKP1U012203F00_	6	15	26.5	22.5	MKP1V011504B00_
3300 "	5	11	18	15	MKP1U012204B00_	6	15	26.5	22.5	MKP1V011505B00_
4700 "	5	11	18	15	MKP1U013304B00_	5	11	18	15	MKP1V012204B00_
6800 "	6	15	26.5	22.5	MKP1U014704B00_	6	15	26.5	22.5	MKP1V012205B00_
	6	15	26.5	22.5	MKP1U014705B00_	5	11	18	15	MKP1V013304B00_
	6	12.5	18	15	MKP1U016804C00_	6	15	26.5	22.5	MKP1V013305B00_
	6	15	26.5	22.5	MKP1U016805B00_	6	12.5	18	15	MKP1V013305B00_
0.01 µF	7	14	18	15	MKP1U021004D00_	6	15	26.5	22.5	MKP1V014704C00_
0.015 "	6	15	26.5	22.5	MKP1U021504F00_	6	15	26.5	22.5	MKP1V014705B00_
0.022 "	8	15	18	15	MKP1U022204J00_	7	16.5	26.5	22.5	MKP1V016804D00_
0.033 "	6	15	26.5	22.5	MKP1U022205D00_	6	15	26.5	22.5	MKP1V016805D00_
0.047 "	9	16	18	15	MKP1U023306A00_	7	16.5	26.5	22.5	MKP1V021005F00_
0.068 "	7	16.5	26.5	22.5	MKP1U024705G00_	8.5	18.5	26.5	22.5	MKP1V021505G00_
	8.5	18.5	26.5	22.5	MKP1U024706B00_	10.5	19	26.5	22.5	MKP1V022205I00_
	9	19	31.5	27.5	MKP1U026805I00_	11	21	26.5	22.5	
	10.5	19	26.5	22.5	MKP1U026806B00_					
	11	21	31.5	27.5						
	11	21	26.5	22.5						
	11	21	31.5	27.5						
0.1 µF	13	24	31.5	27.5	MKP1U031006D00_					
0.15 "	15	26	31.5	27.5	MKP1U031506F00_					
	13	24	41.5	37.5	MKP1U031507C00_					
0.22 "	17	34.5	31.5	27.5	MKP1U032206I00_					
	17	29	41.5	37.5	MKP1U032207E00_					
0.33 "	19	32	41.5	37.5	MKP1U033307F00_					
0.47 "	20	39.5	41.5	37.5	MKP1U034707G00_					
0.68 "	24	45.5	41.5	37.5	MKP1U036807H00_					

\* AC voltage:  $f \leq 1000 \text{ Hz}$ ;  $1.4 \times U_{\text{rms}} + \text{UDC} \leq U_r$

\*\* PCM = Printed circuit module = lead spacing

Dims. in mm.

Ionisation inception level in isolated cases may be lower than admissible rated AC voltage.

Part number completion:

Tolerance: 20 % = M

10 % = K

5 % = J

Packing: bulk = S

Lead length: 6-2 = SD

Taped version see page 127.

Rights reserved to amend design data without prior notification.




Continuation page 61

# WIMA MKP 10






## Continuation

Permissible AC voltage in relation to frequency at 10° C internal temperature rise (general guide).



# WIMA FKP 1

Permissible AC voltage in relation to frequency at 10° C internal temperature rise (general guide).



Technical information and general data see page 66.

## Recommendation for Processing and Application of Through-Hole Capacitors

### Soldering Process

A preheating of through-hole WIMA capacitors is allowed for temperatures  $T_{\max} < 100^{\circ}\text{C}$ . In practice a preheating duration of  $t < 5$  min. has been proven to be best.


#### Single wave soldering

Soldering bath temperature:  $T < 260^{\circ}\text{C}$   
Immersion time:  $t < 5$  sec

#### Double wave soldering

Soldering bath temperature:  $T < 260^{\circ}\text{C}$   
Immersion time:  $2 \times t < 3$  sec

Due to different soldering processes and heat requirements the graphs are to be regarded as a recommendation only.



## WIMA Quality and Environmental Philosophy

### ISO 9001:2000 Certification

ISO 9001:2000 is an international basic standard of quality assurance systems for all branches of industry. The approval according to ISO 9001:2000 of our factories by the VDE inspectorate certifies that organisation, equipment and monitoring of quality assurance in our factories correspond to internationally recognized standards.

### WIMA WPCS

The WIMA Process Control System (WPCS) is a quality surveillance and optimization system developed by WIMA. WPCS is a major part of the quality-oriented WIMA production. Points of application of WPCS during production process:

- incoming material inspection
- metallization
- film inspection
- schoopage
- pre-healing
- lead attachment
- cast resin preparation/encapsulation
- 100% final inspection
- AQL check

### WIMA Environmental Policy

All WIMA capacitors, irrespective of whether through-hole devices or SMD, are made of environmentally friendly materials. Neither during manufacture nor in the product itself any toxic substances are used, e.g.

- Lead
- PCB
- CFC
- Hydrocarbon chloride
- Chromium 6+
- PBB/PBDE
- Arsenic
- Cadmium
- Mercury
- etc.

We merely use pure, recyclable materials for packing our components, such as:

- carton
- cardboard
- adhesive tape made of paper
- polystyrene

We almost completely refrain from using packing materials such as:

- foamed polystyrene (Styropor®)
- adhesive tapes made of plastic
- metal clips

### RoHS Compliance

According to the RoHS Directive 2002/95/EC certain hazardous substances like e.g. lead, cadmium, mercury must not be used any longer in electronic equipment as of July 1st, 2006. For the sake of the environment WIMA has refrained from using such substances since years already.



WIMA Kondensatoren sind bleifrei konform RoHS 2002/95/EG

WIMA capacitors are lead free in accordance with RoHS 2002/95/EC

Tape for lead-free WIMA capacitors

### DIN EN ISO 14001:2005

WIMA's environmental management has been established in accordance with the guidelines of DIN EN ISO 14001:2005. The certification has been granted in June 2006.

# Typical Dimensions for Taping Configuration




Diagram 1:  
PCM 2.5/5/7.5mm

Diagram 2: PCM 10/15 mm

Diagram 3: PCM 22.5 and 27.5\*mm

\*PCM 27.5 taping possible with two feed holes between components

Designation	Symbol	Dimensions for Radial Taping						
		PCM 2.5 taping	PCM 5 taping	PCM 7.5 taping	PCM 10 taping*	PCM 15 taping*	PCM 22.5 taping	PCM 27.5 taping
Carrier tape width	W	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5
Hold-down tape width	W <sub>0</sub>	6.0 for hot-sealing adhesive tape	6.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape
Hole position	W <sub>1</sub>	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5
Hold-down tape position	W <sub>2</sub>	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.
Feed hole diameter	D <sub>0</sub>	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2
Pitch of component	P	12.7 ±1.0	12.7 ±1.0	12.7 ±1.0	25.4 ±1.0	25.4 ±1.0	38.1 ±1.5	38.1 ±1.5 or 50.8 ±1.5
Feed hole pitch	P <sub>0</sub>	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch
Feed hole centre to lead	P <sub>1</sub>	5.1 ±0.5	3.85 ±0.7	2.6 ±0.7	7.7 ±0.7	5.2 ±0.7	7.8 ±0.7	5.3 ±0.7
Hole centre to component centre	P <sub>2</sub>	6.35 ±1.3	6.35 ±1.3	6.35 ±1.3	12.7 ±1.3	12.7 ±1.3	19.05 ±1.3	19.05 ±1.3
Feed hole centre to bottom edge of the component	H	16.5 ±0.3 18.5 ±0.5	16.5 ±0.3 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5
Feed hole centre to top edge of the component	H <sub>1</sub>	H+H <sub>component</sub> < H <sub>1</sub> 32.25 max.	H+H <sub>component</sub> < H <sub>1</sub> 32.25 max.	H+H <sub>component</sub> < H <sub>1</sub> 24.5 to 31.5	H+H <sub>component</sub> < H <sub>1</sub> 25.0 to 31.5	H+H <sub>component</sub> < H <sub>1</sub> 26.0 to 37.0	H+H <sub>component</sub> < H <sub>1</sub> 30.0 to 43.0	H+H <sub>component</sub> < H <sub>1</sub> 35.0 to 45.0
Lead spacing at upper edge of carrier tape	F	2.5 ±0.5	5.0 <sup>+0.8</sup> <sub>-0.2</sub>	7.5 ±0.8	10.0 ±0.8	15 ±0.8	22.5 ±0.8	27.5 ±0.8
Lead diameter	d	0.4 ±0.05	0.5 ±0.05	*0.5 ±0.05 or 0.6 <sup>+0.06</sup> <sub>-0.05</sub>	*0.5 ±0.05 or 0.6 <sup>+0.06</sup> <sub>-0.05</sub>	0.8 <sup>+0.08</sup> <sub>-0.05</sub>	0.8 <sup>+0.08</sup> <sub>-0.05</sub>	0.8 <sup>+0.08</sup> <sub>-0.05</sub>
Component alignment	Δh	± 2.0 max.	± 2.0 max.	± 3.0 max.	± 3.0 max.	± 3.0 max.	± 3.0 max.	± 3.0 max.
Total tape thickness	t	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2
Package (see also page 128)		ROLL/AMMO			AMMO			
		REEL ø 360 max. ø 30 ±1	B 52 ±2 58 ±2 } depending on comp. dimensions		REEL ø 340 max. ø 30 ±1	52 ±2 58 ±2 or 66 ±2	REEL ø 500 max. ø 25 ±1	54 ±2 60 ±2 68 ±2
Unit		see details page 130.						

Dims in mm.

\* Diameter of leads see General Data.

Please clarify customer-specific deviations with the manufacturer.

\* PCM 10 and PCM 15 can be crimped to PCM 7.5.

Position of components according to PCM 7.5 (sketch 11, P<sub>0</sub> = 12.7 or 15.0 is possible)



# Packing Quantities for Bulk Capacitors and TPS\*



PCM	Size				pcs. per packaging unit bulk			pcs. per packaging unit/TPS*	
	W	H	L	Codes	Mini M	Standard S	Maxi G	Mini X	Standard Y
<b>2.5 mm</b>	2.5	7	4.6	<b>0B</b>	1000	5000	10000	-	-
	3	7.5	4.6	<b>0C</b>	1000	5000	10000	-	-
	3.8	8.5	4.6	<b>0D</b>	1000	5000	10000	-	-
	4.6	9	4.6	<b>0E</b>	1000	5000	10000	-	-
	5.5	10	4.6	<b>0F</b>	1000	5000	10000	-	-
<b>5 mm</b>	2.5	6.5	7.2	<b>1A</b>	2000	5000	10000	-	-
	3	7.5	7.2	<b>1B</b>	1000	5000	-	-	-
	3.5	8.5	7.2	<b>1C</b>	1000	5000	-	-	-
	4.5	6	7.2	<b>1D</b>	1000	6000	-	-	-
	4.5	9.5	7.2	<b>1E</b>	1000	4000	-	-	-
	5	10	7.2	<b>1F</b>	1000	3500	-	-	-
	5.5	7	7.2	<b>1G</b>	1000	4000	-	-	-
	5.5	11.5	7.2	<b>1H</b>	500	2500	-	-	-
	6.5	8	7.2	<b>1I</b>	1000	2500	-	-	-
	7.2	8.5	7.2	<b>1J</b>	500	2500	-	-	-
	7.2	13	7.2	<b>1K</b>	500	2000	-	-	-
	8.5	10	7.2	<b>1L</b>	500	2000	-	-	-
	8.5	14	7.2	<b>1M</b>	500	1500	-	-	-
	11	16	7.2	<b>1N</b>	250	1000	-	-	-
<b>7.5 mm</b>	2.5	7	10	<b>2A</b>	1000	5000	-	-	-
	3	8.5	10	<b>2B</b>	1000	5000	-	-	-
	4	9	10	<b>2C</b>	1000	4000	-	-	-
	4.5	9.5	10.3	<b>2D</b>	1000	3500	-	-	-
	5	10.5	10.3	<b>2E</b>	1000	3000	-	-	-
	5.7	12.5	10.3	<b>2F</b>	500	2000	-	-	-
	7.2	12.5	10.3	<b>2G</b>	500	1500	-	-	-
<b>10 mm</b>	3	9	13	<b>3A</b>	1000	3000	-	-	-
	4	8.5	13.5	<b>FA</b>	500	3000	-	-	-
	4	9	13	<b>3C</b>	1000	3000	-	-	-
	4	9.5	13	<b>3D</b>	1000	3000	-	-	-
	5	10	13.5	<b>FB</b>	500	2000	-	-	-
	5	11	13	<b>3F</b>	1000	3000	-	-	-
	6	12	13	<b>3G</b>	800	2400	-	-	-
	6	12.5	13	<b>3H</b>	800	2400	-	-	-
8	12	13	<b>3I</b>	500	2000	-	-	-	
<b>15 mm</b>	5	11	18	<b>4B</b>	800	2400	-	-	-
	5	13	19	<b>FC</b>	200	1000	-	-	-
	6	12.5	18	<b>4C</b>	500	2000	-	-	-
	6	14	19	<b>FD</b>	250	1000	-	-	-
	7	14	18	<b>4D</b>	400	1600	-	-	-
	7	15	19	<b>FE</b>	250	1000	-	-	-
	8	15	18	<b>4F</b>	400	1200	-	-	-
	8	17	19	<b>FF</b>	100	500	-	-	-
	9	14	18	<b>4H</b>	400	1200	-	-	-
	9	16	18	<b>4J</b>	300	900	-	-	-
	10	18	19	<b>FG</b>	100	500	-	-	-
11	14	18	<b>4M</b>	300	1000	-	-	-	
<b>22.5 mm</b>	5	14	26.5	<b>5A</b>	300	1200	-	-	-
	6	15	26.5	<b>5B</b>	250	1000	-	-	-
	7	16.5	26.5	<b>5D</b>	190	760	-	-	-
	8	20	28	<b>FH</b>	125	500	-	-	-
	8.5	18.5	26.5	<b>5F</b>	125	500	-	-	-
	10	22	28	<b>FI</b>	-	-	-	90	540
	10.5	19	26.5	<b>5G</b>	-	-	-	170	680
	10.5	20.5	26.5	<b>5H</b>	-	-	-	170	680
	11	21	26.5	<b>5I</b>	-	-	-	170	680
	12	24	28	<b>FJ</b>	-	-	-	75	450
<b>27.5 mm</b>	9	19	31.5	<b>6A</b>	-	-	-	160	640
	11	21	31.5	<b>6B</b>	-	-	-	136	544
	13	24	31.5	<b>6D</b>	-	-	-	112	448
	13	25	33	<b>FK</b>	-	-	-	56	336
	15	26	31.5	<b>6F</b>	-	-	-	96	384
	15	26	33	<b>FL</b>	-	-	-	48	288
	17	29	31.5	<b>6G</b>	-	-	-	88	176
	17	34.5	31.5	<b>6I</b>	-	-	-	88	176
	20	32	33	<b>FM</b>	-	-	-	36	216
	20	39.5	31.5	<b>6J</b>	-	-	-	36	144
<b>37.5 mm</b>	9	19	41.5	<b>7A</b>	-	-	-	60	480
	11	22	41.5	<b>7B</b>	-	-	-	51	408
	13	24	41.5	<b>7C</b>	-	-	-	84	252
	15	26	41.5	<b>7D</b>	-	-	-	72	144
	17	29	41.5	<b>7E</b>	-	-	-	66	132
	19	32	41.5	<b>7F</b>	-	-	-	54	108
	20	39.5	41.5	<b>7G</b>	-	-	-	27	108
	24	45.5	41.5	<b>7H</b>	-	-	-	21	84

Rights reserved to amend design data without prior notification.  
Samples and pre-production needs on request.

■ Moulded versions.

\* Tray-Packing-System

# Packing Units for Taped Capacitors with Radial Leads



PCM	Size				ROLL		REEL				AMMO			
					H16.5	H18.5	ø 360		ø 500		340 × 340		490 × 370	
	W	H	L	Codes	N	O	F	I	H	J	A	C	B	D
<b>2.5 mm</b>	2.5	7	4.6	<b>0B</b>	2200		2500				2800			
	3	7.5	4.6	<b>0C</b>	2000		2300				2300			
	3.8	8.5	4.6	<b>0D</b>	1500		1800				1800			
	4.6	9	4.6	<b>0E</b>	1200		1500				1500			
	5.5	10	4.6	<b>0F</b>	900		1200				1200			
<b>5 mm</b>	2.5	6.5	7.2	<b>1A</b>	2200		2500				2800			
	3	7.5	7.2	<b>1B</b>	2000		2300				2300			
	3.5	8.5	7.2	<b>1C</b>	1600		2000				2000			
	4.5	6	7.2	<b>1D</b>	1300		1500				1500			
	4.5	9.5	7.2	<b>1E</b>	1300		1500				1500			
	5	10	7.2	<b>1F</b>	1100		1400				1400			
	5.5	7	7.2	<b>1G</b>	1000		1200				1200			
	5.5	11.5	7.2	<b>1H</b>	1000		1200				1200			
	6.5	8	7.2	<b>1I</b>	800		1000				1000			
	7.2	8.5	7.2	<b>1J</b>	700		1000				1000			
	7.2	13	7.2	<b>1K</b>	700		950				1000			
	8.5	10	7.2	<b>1L</b>	600		800				800			
8.5	14	7.2	<b>1M</b>	600		800				800				
11	16	7.2	<b>1N</b>	500		700				700				
<b>7.5 mm</b>	2.5	7	10	<b>2A</b>	-		2500		4400		2500			
	3	8.5	10	<b>2B</b>	-		2200		4300		2300		4150	
	4	9	10	<b>2C</b>	-		1700		3200		1700		3100	
	4.5	9.5	10.3	<b>2D</b>	-		1500		2900		1400		2800	
	5	10.5	10.3	<b>2E</b>	-		1300		2500		1300		-	
	5.7	12.5	10.3	<b>2F</b>	-		1000		2200		1100		-	
	7.2	12.5	10.3	<b>2G</b>	-		900		1800		1000		-	
<b>10 mm</b>	3	9	13	<b>3A</b>	-		1100		2200		-		1900	
	4	8.5	13.5	<b>3A</b>	-		900		1600		-		1450	
	4	9	13	<b>3C</b>	-		900		1600		-		1450	
	4	9.5	13	<b>3D</b>	-		900		1600		-		1400	
	5	10	13.5	<b>3B</b>	-		700		1300		-		1200	
	5	11	13	<b>3F</b>	-		700		1300		-		1200	
	6	12	13	<b>3G</b>	-		550		1100		-		1000	
	6	12.5	13	<b>3H</b>	-		550		1100		-		1000	
8	12	13	<b>3I</b>	-		400		800		-		740		
<b>15 mm</b>	5	11	18	<b>4B</b>	-		600		1200		-		1150	
	5	13	19	<b>4B</b>	-		600		1200		-		1200	
	6	12.5	18	<b>4C</b>	-		500		1000		-		1000	
	6	14	19	<b>4D</b>	-		500		1000		-		1000	
	7	14	18	<b>4D</b>	-		450		900		-		850	
	7	15	19	<b>4E</b>	-		450		900		-		850	
	8	15	18	<b>4F</b>	-		400		800		-		740	
	8	17	19	<b>4F</b>	-		400		800		-		740	
	9	14	18	<b>4H</b>	-		350		700		-		650	
	9	16	18	<b>4J</b>	-		350		700		-		650	
10	18	19	<b>4G</b>	-		300		650		-		590		
11	14	18	<b>4M</b>	-		300		600		-		540		
<b>22.5 mm</b>	5	14	26.5	<b>5A</b>	-		-		800		-		770	
	6	15	26.5	<b>5B</b>	-		-		700		-		640	
	7	16.5	26.5	<b>5D</b>	-		-		600		-		550	
	8	20	28	<b>5H</b>	-		-		500		-		480	
	8.5	18.5	26.5	<b>5F</b>	-		-		480		-		450	
	10	22	28	<b>5I</b>	-		-		420		-		380	
	10.5	19	26.5	<b>5G</b>	-		-		400		-		360	
	10.5	20.5	26.5	<b>5H</b>	-		-		400		-		360	
11	21	26.5	<b>5I</b>	-		-		380		-		350		
12	24	28	<b>5J</b>	-		-		350		-		310		
<b>27.5 mm</b>	9	19	31.5	<b>6A</b>	-		-		460/340*		-		420	
	11	21	31.5	<b>6B</b>	-		-		380/280*		-		350	
	13	24	31.5	<b>6D</b>	-		-		300		-		290	
	15	26	31.5	<b>6F</b>	-		-		270		-		250	

\* for 2-inch transport pitches.

Samples and pre-production needs 1 packing unit minimum.

■ Moulded versions.

Rights reserved to amend design data without prior notification.



A WIMA part number consists of 18 digits and is composed as follows:

- Field 1 - 4: Type description
- Field 5 - 6: Rated voltage
- Field 7 - 10: Capacitance
- Field 11 - 12: Size and PCM
- Field 13 - 14: Special features (e.g. Snubber versions)
- Field 15: Capacitance tolerance
- Field 16: Packing
- Field 17 - 18: Lead length (untaped)

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
<b>M</b>	<b>K</b>	<b>S</b>	<b>2</b>	<b>C</b>	<b>0</b>	<b>2</b>	<b>1</b>	<b>0</b>	<b>0</b>	<b>1</b>	<b>A</b>	<b>0</b>	<b>0</b>	<b>M</b>	<b>S</b>	<b>S</b>	<b>D</b>
MKS 2				63 VDC		0.01 µF			2.5x6.5x7.2			-		20%	bulk	6-2	

<p><b>Type description:</b></p> <p>SMD-PET = SMDT                  SMD-PPS = SMDI                  FKP 02 = FKP0                  MKS 02 = MKS0                  FKS 2 = FKS2                  FKP 2 = FKP2                  MKS 2 = MKS2                  MKP 2 = MKP2                  FKS 3 = FKS3                  FKP 3 = FKP3                  MKS 4 = MKS4                  MKP 4 = MKP4                  MKP 10 = MKP1                  FKP 4 = FKP4                  FKP 1 = FKP1                  MKP-X2 = MKX2                  MKP-X2 R = MKXR                  MKP-Y2 = MKY2                  MP 3-X2 = MPX2                  MP 3-X1 = MPX1                  MP 3-Y2 = MPY2                  MP 3R-Y2 = MPRY                  Snubber MKP = SNMP                  Snubber FKP = SNFP                  GTO MKP = GTOM                  DC-LINK MKP 4 = DCP4                  DC-LINK MKP C = DCPC                  DC-LINK HC = DCH_                  SuperCap C = SCS C                  SuperCap MC = SCSMC                  SuperCap R = SCSR                  SuperCap MR = SCSMR</p>	<p><b>Rated voltage:</b></p> <p>2.5 VDC = A1                  4 VDC = A2                  14 VDC = A3                  28 VDC = A4                  40 VDC = A5                  5 VDC = A6                  50 VDC = B0                  63 VDC = C0                  100 VDC = D0                  160 VDC = E0                  250 VDC = F0                  400 VDC = G0                  450 VDC = H0                  600 VDC = I0                  630 VDC = J0                  700 VDC = K0                  800 VDC = L0                  850 VDC = M0                  900 VDC = N0                  1000 VDC = O1                  1100 VDC = P0                  1200 VDC = Q0                  1250 VDC = R0                  1500 VDC = S0                  1600 VDC = T0                  2000 VDC = U0                  2500 VDC = V0                  3000 VDC = W0                  4000 VDC = X0                  6000 VDC = Y0                  250 VAC = 0W                  275 VAC = 1W                  300 VAC = 2W                  400 VAC = 3W                  440 VAC = 4W                  500 VAC = 5W                  ...</p>	<p><b>Capacitance:</b></p> <p>22 pF = 0022                  47 pF = 0047                  100 pF = 0100                  150 pF = 0150                  220 pF = 0220                  330 pF = 0330                  470 pF = 0470                  680 pF = 0680                  1000 pF = 1100                  1500 pF = 1150                  2200 pF = 1220                  3300 pF = 1330                  4700 pF = 1470                  6800 pF = 1680                  0.01 µF = 2100                  0.022 µF = 2220                  0.047 µF = 2470                  0.1 µF = 3100                  0.22 µF = 3220                  0.47 µF = 3470                  1 µF = 4100                  2.2 µF = 4220                  4.7 µF = 4470                  10 µF = 5100                  22 µF = 5220                  47 µF = 5470                  100 µF = 6100                  220 µF = 6220                  1 F = A010                  2.5 F = A025                  50 F = A500                  100 F = B100                  110 F = B110                  600 F = B600                  1200 F = C120                  ...</p>	<p><b>Size:</b></p> <p>4.8x3.3x3 Size 1812 = X1                  4.8x3.3x4 Size 1812 = X2                  5.7x5.1x3.5 Size 2220 = Y1                  5.7x5.1x4.5 Size 2220 = Y2                  7.2x6.1x3 Size 2824 = T1                  7.2x6.1x5 Size 2824 = T2                  10.2x7.6x5 Size 4030 = K1                  12.7x10.2x6 Size 5040 = V1                  15.3x13.7x7 Size 6054 = Q1                  2.5x7x4.6 PCM2.5 = 0B                  3x7.5x4.6 PCM2.5 = 0C                  2.5x6.5x7.2 PCM5 = 1A                  3x7.5x7.2 PCM5 = 1B                  2.5x7x10 PCM7.5 = 2A                  3x8.5x10 PCM7.5 = 2B                  3x9x13 PCM10 = 3A                  4x9x13 PCM10 = 3C                  5x11x18 PCM15 = 4B                  6x12.5x18 PCM15 = 4C                  5x14x26.5 PCM22.5 = 5A                  6x15x26.5 PCM22.5 = 5B                  9x19x31.5 PCM27.5 = 6A                  11x21x31.5 PCM27.5 = 6B                  9x19x41.5 PCM37.5 = 7A                  11x22x41.5 PCM37.5 = 7B                  94x49x182 DCH_ = H0                  94x77x182 DCH_ = H1                  ...</p> <p><b>Special features:</b></p> <p>Standard = 00                  Version A1 = 1A                  Version A1.1.1 = 1B                  Version A1.2 = 1C                  ...</p>	<p><b>Tolerance:</b></p> <p>20% = M                  10% = K                  5% = J                  2.5% = H                  1% = E                  ...</p> <p><b>Packing:</b></p> <p>AMMO H16.5 340x340 = A                  AMMO H16.5 490x370 = B                  AMMO H18.5 340x340 = C                  AMMO H18.5 490x370 = D                  REEL H16.5 360 = F                  REEL H16.5 500 = H                  REEL H18.5 360 = I                  REEL H18.5 500 = J                  ROLL H16.5 = N                  ROLL H18.5 = O                  BLISTER W12 180 = P                  BLISTER W12 330 = Q                  BLISTER W16 330 = R                  BLISTER W24 330 = T                  Bulk Mini = M                  Bulk Standard = S                  Bulk Maxi = G                  TPS Mini = X                  TPS Standard = Y                  ...</p> <p><b>Lead length (untaped)</b></p> <p>3.5 ±0.5 = C9                  6-2 = SD                  16 ±1 = P1                  ...</p>
--	---	---	--	--

The data on this page is not complete and serves only to explain the part number system. Part number information is listed on the pages of the respective WIMA range.