

This document was generated on 05/10/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

	nale Fully Insulated Quick Disconnect Flag for 14-16 AWG Wire, Tab .813mm (.032"), 94 V-0 Material	Cartan 1
Documents: Drawing (PDF) Product Specification PS-19902-008 (PD Product Specification PS-19902-011 (PD		Series
Agency Certification		image - Reference only
UL	E79133	
General Product Family Series Crimp Quality Equipment Product Name Type	Quick Disconnects <u>19007</u> Yes InsulKrimp™ Quick Disconnect	EU RoHS China RoHS ELV and RoHS Compliant REACH SVHC Not Reviewed Low-Halogen Status Not Reviewed
Physical		Need more information on product
Barrel Type	Closed	environmental compliance?
Color - Resin	Natural	Email productcompliance@molex.com
Flammability	94V-0	For a multiple part number RoHS Certificate
Gender	Female	Compliance, click here
Glow-Wire Compliant	No	Compliance, <u>click here</u>
Insulation	Nylon (PA)	Please visit the Contact Us section for any
Lock to Mating Part	None	non-product compliance questions.
Material - Metal	Brass	
Material - Resin	Nylon	
Orientation	Flag	
Packaging Type	Bag	Search Parts in this Series
Polarized to Mating Part	No	19007Series
Tab Thickness	0.81mm (.032")	
Tab Width	6.35mm (.250")	Application Tooling FAQ
Temperature Range - Operating	-65°C to +105°C	Tooling specifications and manuals are
Wire Insulation Diameter	5.08mm (.200")	found by selecting the products below.
Wire Size AWG	14, 16	Crimp Height Specifications are then
Wire Size mm ²	1.00 - 2.60	contained in the Application Tooling
Electrical		Specification document.
Voltage - Maximum	600V	Description Product #
Material Info		Hand Crimp Tool <u>0640014100</u>
Old Part Number	BB-2221V	· · · ·
Potoronco - Drawing Numbers		
Reference - Drawing Numbers		
Product Specification Sales Drawing	PS-19902-008, PS-19902-011, PS-19902-013 SD-19007-002	

This document was generated on 05/10/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION