www.schurter.com/pg07\_2

# CN Power Supply Cord with IEC Connector C13, V-Lock, straight











### Description

- Power Cord, Protection class I, Pin temperature 70 °C,
- with V-Lock interlocking system

## References

# Weblinks

pdf, html, General Product Information, Approvals, RoHS, CHINA-RoHS, Mating Connectors, e-Store, SCHURTER-Stock-Check, Distributor-Stock-Check, Accessories

Technical Data	
Ratings UL/CSA	10 A / 250 VAC; 50/60 Hz
Dielectric Strength	> 2kVDC between L-N
	> 2 kVAC between L/N-PE
	(1 min/50 Hz)
Allowable Operation Temp.	-25 °C to 75 °C
Degree of Protection	from front side IP 20 acc. to IEC 60529
Protection Class	Suitable for appliances with protection
	class 1 acc. to IEC 61140
Terminal	moulded

PVC, black

Connector	C13 acc. to IEC/EN 60320-2-2
	UL 498, CSA C22.2 no. 42 (for cold
	conditions) pin-temperature 70 °C, 10A,
	Protection Class 1

# **Variants**

Material: Housing

Connect	or	cable			inlets						Order Number
Туре	V-Lock	Cord Type	Color	Length [m]	Туре	Country	Standard	Conductor cross section	Style	Index	
C13	•	RW 300/500 3x1.0	black	2.0	China	CN	GB 2099	3 x 1 mm²	-	-	6051.2032

Packaging unit 100 Pcs

## **Mating Inlets/Plugs**

### Category / Description

# Appliance InletOverview complete



IEC Appliance Inlet C14, Snap-in Mounting, Solder, Quick-connect, Screw or PCB Terminal	6010	
IEC Appliance Inlet C14, Screw-on Mounting, Front Side, Solder or Quick-connect, PCB or Screw Terminal	6061	
IEC Appliance Inlet C14, Screw-on Mounting, Front Side, Solder or Quick-connect or Screw Terminal	6062	
IEC Appliance Inlet C14, insert Mounting, Solder or Quick-connect, PCB or Screw Terminal	6170	
IEC Appliance Inlet C14 or C18, Screw-on Mounting, Rear Side, PCB- or Solder Terminal	GSP1	
Appliance Inletfurther types toV/AC1 3KS		

### www.schurter.com/pg07 2



### Power Entry ModuleOverview complete

Power Entry Module with line filterOverview complete

IEC Appliance Inlet C14 with Fuseholder 2-pole	4707
IEC Appliance Inlet C14 with Line Switch 1- or 2-pole	DC11
IEC Appliance Inlet C14 with recessed Circuit Breaker TA45	DF11
IEC Appliance Inlet C14 with Fuseholder 1- or 2-pole, Line Switch 1- or 2-pole and Voltage Selector	KD
* * * * * * * * * * * * * * * * * * * *	
IEC Appliance Inlet C14 with Line Switch 2-pole	KEB2




IEC Appliance Inlet C14 or C18 with Filter, ECO design, Front- or Rear Side Mounting 5120 IEC Appliance Inlet C14 or C18 with Filter, Protection Degree IP65, Fuseholder 1- or 2-pole, Front or Rear Mounting 5707 IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole (5x20 mm or 6.3x32 mm), Line Switch 1- or 2-pole, Vol-CD tage Selector (Step) IEC Appliance Inlet C14 with Filter, Line Switch 1- or 2-pole, Front or Rear Side Mounting DC12 IEC Appliance Inlet C14 with Filter, Line Switch 1-pole KFB1 Power Entry Module with line filterfurther types toVAC13KS

### Passende Stecker verriegelt zu



### Appliance InletOverview complete





### Power Entry ModuleOverview complete

IEC Appliance Inlet C14 with Fuseholder 2-pole	4707	
IEC Appliance Inlet C14 with Line Switch 1- or 2-pole	DC11	
IEC Appliance Inlet C14 with recessed Circuit Breaker TA45	DF11	
IEC Appliance Inlet C14 with Fuseholder 1- or 2-pole, Line Switch 1- or 2-pole and Voltage Selector	KD	
IEC Appliance Inlet C14 with Line Switch 2-pole	KEB2	
Power Entry Modulefurther types toVAC13KS		





IEC Appliance Inlet C14 or C18 with Filter, ECO design, Front- or Rear Side Mounting	5120
IEC Appliance Inlet C14 or C18 with Filter, Protection Degree IP65, Fuseholder 1- or 2-pole, Front or Rear Mo	ounting 5707
IEC Appliance Inlet C14 with Filter, Fuseholder 1- or 2-pole (5x20 mm or 6.3x32 mm), Line Switch 1- or 2-ptage Selector (Step)	oole, Vol-
IEC Appliance Inlet C14 with Filter, Line Switch 1- or 2-pole, Front or Rear Side Mounting	DC12
IEC Appliance Inlet C14 with Filter, Line Switch 1-pole	KFB1
Power Entry Module with line filterfurther types toVAC13KS	