

Advanced temperature controller for thermoelectrics

The PR-59 temperature controller is designed for reversible (cooling/heating) control of thermoelectric assemblies/systems with high temperature accuracy.

The controller not only regulates the temperature, but also features two programmable fan outputs and an alarm output relay. The RS232 interface allows you to read and control parameters and settings in real-time. However, the con-

troller can also be used as a stand-alone unit. An easy-to-use PC software for programming of the controller is included.

Typical applications include analytical instruments, cooling of lasers, thermocyclers and medical equipment.



Laird
TECHNOLOGIES®

Innovative **Technology**
for a **Connected** World

Features of PR-59:

- Input voltage from 10 to 30 Volts DC
- Handling load up to 15A at 30 VDC
30A at 30 VDC with additional cooling
- Bi-directional control for heating or cooling applications, using "H" bridge
- PC Programmable via RS232 communications interface with easy-to-use PC program. The advanced Graphical User Interface (GUI) shows temperatures etc. in real-time while setting parameters. Different setups can easily be saved.
- Regulator Proportional (P), Integral (I), Derivative (D) control, selectable; P, PI, PD, PID or ON/OFF mode; all parameters adjustable.
- Real-time control of regulator parameters and temperature readings via RS232 interface.
- Control temperature, from -20°C to +100°C (-4 to +212°F) with the standard NTC sensor. Other temperature range possible with other (NTC, PT1000) sensors.
- Two FAN control outputs, with independent regulator control: ON/OFF or ALGO mode. All parameters adjustable.
- Temperature resolution of max 0.05°C
- Pulse width modulation of output:
 - Base Frequency of 10kHz
 - Control Stability of $\pm 0.05^{\circ}\text{C}$ (-20 C to + 50 C)
- Set Temperature Selectable
 - PC set with controller stand alone operation
 - Remote user set temperature potentiometer
 - 0 to 5 VDC adjustable range
- Two alarm temperature sensor inputs with adjustable alarm set points
- Alarm relay output, normally closed (will open on alarm); 1A @ 24VDC/120 VAC
- Alarm configuration, adjustable set points:
 - Under or over voltage check
 - Output current overload check
 - FAN not connected or not working check
 - Temperature sensor not connected or short circuit check
 - Over or under temperature check
- All parameters storable in FLASH non-volatile memory
- Firmware download via RS232. Gives you access to new features in the future.

global solutions: local support™

Americas: +1.888.246.9050

Europe: +46.31.704.67.57

Asia: +86.755.2714.1166

CLV-customerservice@lairdtech.com

www.lairdtech.com/thermal

THR-DS-TEMPERATURE-CONTROLLERS 0709

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2009 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.