



EMIFIL® (Inductor type) Chip Ferrite Bead (Array)

BLA31A/BLA31B Series (1206 Size)

■ Dimensions



■ Equivalent Circuit



■ Packaging

Code	Packaging	Minimum Quantity
D	180mm Paper Tape	4000
J	330mm Paper Tape	10000
B	Bulk(Bag)	1000

■ Rated Value (□: packaging code)

Part Number	Impedance (at 100MHz/20°C)	Impedance (at 1GHz/20°C)	Rated Current	DC Resistance	Operating Temperature Range
BLA31AG300SN4□	30ohm±25%	-	200mA	0.10ohm max	-55 to +125°C
BLA31AG600SN4□	60ohm±25%	-	200mA	0.15ohm max	-55 to +125°C
BLA31AG121SN4□	120ohm±25%	-	150mA	0.20ohm max	-55 to +125°C
BLA31AG221SN4□	220ohm±25%	-	150mA	0.25ohm max	-55 to +125°C
BLA31AG601SN4□	600ohm±25%	-	100mA	0.35ohm max	-55 to +125°C
BLA31AG102SN4□	1000ohm±25%	-	50mA	0.45ohm max	-55 to +125°C
BLA31BD121SN4□	120ohm±25%	-	150mA	0.30ohm max	-55 to +125°C
BLA31BD221SN4□	220ohm±25%	-	150mA	0.35ohm max	-55 to +125°C
BLA31BD471SN4□	470ohm±25%	-	100mA	0.40ohm max	-55 to +125°C
BLA31BD601SN4□	600ohm±25%	-	100mA	0.45ohm max	-55 to +125°C
BLA31BD102SN4□	1000ohm±25%	-	50mA	0.55ohm max	-55 to +125°C

Number of Circuits: 4

Continued on the following page.

● This data sheet is applied for CHIP FERRITE BEAD used for General Electronics equipment for your design.


⚠ Note:

1. This datasheet is downloaded from the website of Murata Manufacturing co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.

Continued from the preceding page.


Impedance-Frequency Characteristics (Main Items)

BLA31AG Series




Impedance-Frequency Characteristics (Main Items)

BLA31BD Series




Impedance-Frequency Characteristics

BLA31AG300SN4




Impedance-Frequency Characteristics

BLA31AG600SN4




Impedance-Frequency Characteristics

BLA31AG121SN4



Impedance-Frequency Characteristics

BLA31AG221SN4



Continued on the following page.

This data sheet is applied for CHIP FERRITE BEAD used for General Electronics equipment for your design.


Note:

- This datasheet is downloaded from the website of Murata Manufacturing co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.

Continued from the preceding page.


Impedance-Frequency Characteristics

BLA31AG601SN4




Impedance-Frequency Characteristics

BLA31AG102SN4




Impedance-Frequency Characteristics

BLA31BD121SN4




Impedance-Frequency Characteristics

BLA31BD221SN4




Impedance-Frequency Characteristics

BLA31BD471SN4



Impedance-Frequency Characteristics

BLA31BD601SN4



Continued on the following page. ↗

● This data sheet is applied for CHIP FERRITE BEAD used for General Electronics equipment for your design.


⚠ Note:

1. This datasheet is downloaded from the website of Murata Manufacturing co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.

Continued from the preceding page.

■ Impedance-Frequency Characteristics

BLA31BD102SN4



■ ⚠ Caution/Notice

⚠ Caution (Rating)

Do not use products beyond the rated current as this may create excessive heat and deteriorate the insulation resistance.

Notice

Solderability of Tin plating termination chip might be deteriorated when low temperature soldering profile where peak solder temperature is below the Tin melting point is used. Please confirm the solderability of Tin plating termination chip before use.

● This data sheet is applied for CHIP FERRITE BEAD used for General Electronics equipment for your design.

⚠ Note:

1. This datasheet is downloaded from the website of Murata Manufacturing co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
2. This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.