


HR2220P601R-10

UNCONTROLLED DOCUMENT

PHYSICAL DIMENSIONS:


A	5.59 [.220]	+ 0.51 [.020]
B	5.08 [.200]	+ 0.25 [.010]
C	3.05 [.120]	+ 0.25 [.010]
D	0.76 [.030]	+ 0.25 [.010]




ELECTRICAL CHARACTERISTICS:			
Z @ 100MHz (Ω)	DCR (Ω)	Rated Current	
Nominal	600		
Minimum	450		
Maximum	750	0.025	4000 mA

NOTES: UNLESS OTHERWISE SPECIFIED

1. TAPED AND REELED per CURRENT EIA SPECIFICATIONS 13" REELS, 2,000 PCS/REEL.
2. U.S. PATENTS 5,821,846, 6,107,907, AND 6,249,205B1 SHOULD APPEAR ON THE LABEL OF EACH REEL OF PACKAGED PARTS.
3. TERMINATION FINISH IS 100% TIN.
4. COMPONENTS SHOULD BE ADEQUATELY PREHEATED BEFORE SOLDERING.





LAND PATTERNS FOR REFLOW SOLDERING



(For wave soldering, add 0.762 [.030] to this dimension.)

RECOMMENDED SOLDERING CONDITIONS



AGILENT E4991A RF Impedance/Material Analyzer
HP 16194A Test Fixture. TEST REF. 3298



DIMENSIONS ARE IN mm [INCHES].		This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.	
		Laird TECHNOLOGIES	
PROJECT/PART NUMBER: HR2220P601R-10		REV: B	PART TYPE: CO-FIRE
DATE: 04/03/04		SCALE: NTS	DRAWN BY: TMB
REV: A	DESCRIPTION: ORIGINAL DRAFT	DATE: 04/03/04	SHEET: 2 of 2
REV: B	DESCRIPTION: UPDATE COMPANY LOGO ADD ROHS	DATE: 02/14/08	TOOL #: -