

"High Frequency Ceramic Solutions"

5.5 GHz Band Pass Filter

P/N 5515BP15B725

Detail Specification 02/07/03



Page 1 of 2

Part Number	Frequency (MHz)	Insertion Loss	Attenuation (min.)	Return Loss
5515BP15B725_	5150 - 5875	1.5 dB max.	30 dB @ 3500 MHz	9.5 dB min.

Input Power	Impedance	Operating Temperature Range
500 mW max	50 Ω	-40 to +85°C


Mechanical Dimensions

	L	W	T	a	b	c	d
Inches	0.079 ± .006	0.049 ± .004	0.037 ± .004	0.051 ± .006	0.012 ± .006	0.010 ± .006	0.014 ± .006
mm	2.0 ± 0.15	1.25 ± 0.10	0.95 ± 0.10	1.30 ± 0.15	0.30 ± 0.15	0.25 ± 0.15	0.35 ± 0.15



Terminal Configuration


No.	Function	No.	Function
1	GND	3	GND
2	OUT	4	IN



Mounting Considerations

- Mount these devices with brown mark facing up.
- Line width should be designed to provide 50 Ω impedance matching characteristics.

Units: mm



Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.

“High Frequency Ceramic Solutions”


5.5 GHz Band Pass Filter

Detail Specification 02/07/03

P/N 5515BP15B725

Page 2 of 2

Typical Insertion Loss / Return Loss



Delivery

Packaged in embossed tape on 7" reels (3000 / reel)
Standard delivery is eight weeks or sooner ARO