



SAW Components

Data Sheet B3804





SAW Components

B3804

Low-Loss Filter

170,2 MHz

Data Sheet


Features

- Low-loss IF filter for GSM base station
- Temperature stable
- Ceramic SMD package

Terminals

- Gold plated


Ceramic package DCC18



Dimensions in mm, approx. weight 0,8 g

Pin configuration

- | | |
|------------|----------------------------------|
| 10 | Input or balanced input |
| 1 | Input ground or balanced input |
| 5 | Output or balanced output |
| 6 | Output ground or balanced output |
| 3, 8 | Ground |
| 2, 4, 7, 9 | Case ground |



Type	Ordering code	Marking and Package according to	Packing according to
B3804	B39171-B3804-U210	C61157-A7-A54	F61074-V8081-Z000

Electrostatic Sensitive Device (ESD)

Maximum ratings

Operable temperature range	T	-40 / +85	°C
Storage temperature range	T_{stg}	-40 / +85	°C
DC voltage	V_{DC}	0	V
Source power	P_s	10	dBm



SAW Components	B3804
Low-Loss Filter	170,2 MHz

Data Sheet

Characteristics


Operating temperature range:	$T = -10 \dots 85 \text{ }^\circ\text{C}$
Terminating source impedance:	$Z_S = 50 \text{ } \Omega$ unbalanced or $200 \text{ } \Omega$ balanced and matching network
Terminating load impedance:	$Z_L = 50 \text{ } \Omega$ unbalanced or $200 \text{ } \Omega$ balanced and matching network

		min.	typ.	max.	
Nominal frequency	f_N	—	170,2	—	MHz
Minimum insertion attenuation	α_{\min}	—	6,5	7,5	dB
Amplitude ripple (p-p)	$\Delta\alpha$				
	$f_N \pm 135 \text{ kHz}$	—	0,35	0,7	dB
Group delay ripple (p-p)	$\Delta\tau$				
	$f_N \pm 135 \text{ kHz}$	—	0,35	0,7	μs
Relative attenuation (relative to α_{\min})	α_{rel}				
	$f_N \pm 0,35 \text{ MHz} \dots f_N \pm 0,6 \text{ MHz}$	7	11	—	dB
	$f_N \pm 0,6 \text{ MHz} \dots f_N \pm 0,8 \text{ MHz}$	24	30	—	dB
	$f_N \pm 0,8 \text{ MHz} \dots f_N \pm 1,6 \text{ MHz}$	40	45	—	dB
	$f_N \pm 1,6 \text{ MHz} \dots f_N \pm 20,0 \text{ MHz}$	43	50	—	dB
	$f_N \pm 20,0 \text{ MHz} \dots f_N \pm 35,0 \text{ MHz}$	50	55	—	dB
	$f_N \pm 35,0 \text{ MHz} \dots f_N \pm 75,0 \text{ MHz}$	45	60	—	dB
	$f_N + 23,5 \text{ MHz} \dots f_N + 23,7 \text{ MHz}$	55	60	—	dB
	$f_N + 75,0 \text{ MHz} \dots f_N + 2,0 \text{ GHz}$	40	60	—	dB
VSWR (Input and output)	$f_N \pm 135 \text{ kHz}$	—	1,5	2,0	
Temperature coefficient of frequency ¹⁾	TC_f	—	-0,036	—	ppm/K ²
Turnover temperature	T_0	—	45	—	$^\circ\text{C}$

¹⁾ Temperature dependance of f_c : $f_c(T_A) = f_c(T_0)(1 + TC_f(T_A - T_0)^2)$

Data Sheet
Matching network to 50 Ω unbalanced

(Element values depend upon PCB layout)



$$C_{p1} = 36,3 \text{ pF}$$


$$L_{s2} = 39,0 \text{ nH}$$

$$L_{s3} = 39,0 \text{ nH}$$

$$C_{p4} = 36,3 \text{ pF}$$

Matching network to 200 Ω balanced

(Element values depend upon PCB layout)



$$C_{p1} = 17,7 \text{ pF}$$

$$L_{s2} = 27,0 \text{ nH}$$


$$L_{s3} = 27,0 \text{ nH}$$

$$C_{p4} = 17,7 \text{ pF}$$




Data Sheet

Normalized frequency response



Normalized frequency response (passband)





SAW Components


B3804

Low-Loss Filter

170,2 MHz

Data Sheet

Transfer function





SAW Components

B3804

Low-Loss Filter

170,2 MHz

Data Sheet

Published by EPCOS AG
Surface Acoustic Wave Components Division, SAW MC IS
P.O. Box 80 17 09, D-81617 München

© EPCOS AG 1999. All Rights Reserved.

As far as patents or other rights of third parties are concerned, liability is only assumed for components per se, not for applications, processes and circuits implemented within components or assemblies.

The information describes the type of component and shall not be considered as assured characteristics.

Terms of delivery and rights to change design reserved.

For questions on technology, prices and delivery please contact the sales offices of EPCOS AG or the international representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our sales offices.