





Designers' Choice

THREADED STANDOFFS



HEX



ROUND



MATERIAL

Brass: per ASTM-B16
Aluminum: QQ-A-225/3, Alloy 2011-T3

PLATING

Zinc: ASTM B633
Iridite Finish: MIL-C-5541

THREAD	O.D.	LENGTH	ALUMINUM IRIDITE FINISH		BRASS ZINC PLATE			
			HEX CAT. NO.	ROUND CAT. NO.	HEX CAT. NO.	ROUND CAT. NO.		
2-56	.156 (5/32)	3/16 (.187)	1797A	1801A	1798A	1802A		
		1/4 (.250)	1797B	1801B	1798B	1802B		
		5/16 (.312)	1797C	1801C	1798C	1802C		
		3/8 (.375)	1797D	1801D	1798D	1802D		
4-40	.187 (3/16)	1/4 (.250)	1891	2025	1450	1547		
		3/8 (.375)	1892	2026	1803	1864		
		1/2 (.500)	1893	2027	1656	1657		
		5/8 (.625)	1894	2028	1804	1865		
		3/4 (.750)	1895	2029	1656A	1657A		
		7/8 (.875)	1896	2030	1805	1866		
		1 (1.000)	1897	2031	1656B	1657B		
		1-1/2 (1.500)	2201	3478	1450A	1547A		
4-40	.250 (1/4)	3/8 (.375)	2202	3479	1450B	1547B		
		1/2 (.500)	2203	3480	1450C	1547C		
		5/8 (.625)	1808	1839	1829	1867		
		3/4 (.750)	2204	3481	1450D	1547D		
		7/8 (.875)	1809	1846	1830	1876		
		1 (1.000)	2205	3482	1450E	1547E		
		1-1/2 (1.500)	2206	3483	1831	1877		
		2 (2.000)	2207	3484	1832	1878		
		6-32	.250 (1/4)	1/4 (.250)	2208	3485	1451A	1548A
				3/8 (.375)	2209	3486	1451B	1548B
1/2 (.500)	2210			3487	1451C	1548C		
5/8 (.625)	1813			1847	1451D	1548D		
3/4 (.750)	2211			3488	1451E	1548E		
7/8 (.875)	1816			1848	1833	1879		
1 (1.000)	2212			3489	1635	1548F		
1-1/4 (1.250)	1818			1853	1636	1881		
1-1/2 (1.500)	2213			3490	1637	1882		
1-3/4 (1.750)	1819			1855	1638	1883		
2 (2.000)	2214			3491	1639	1884		
2-1/4 (2.250)	1820			1856	1642	1885		
2-1/2 (2.500)	1825			1857	1643	1886		
8-32	.250 (1/4)			1/4 (.250)	2215	3492	1474A	1692A
		3/8 (.375)	2216	3493	1474B	1692B		
		1/2 (.500)	2217	3494	1474C	1692C		
		5/8 (.625)	1827	1858	1834	1887		
		3/4 (.750)	2218	3495	1474D	1692D		
		7/8 (.875)	1828	1859	1836	1888		
		1 (1.000)	2219	3496	1474E	1692E		
		1-1/2 (1.500)	2220	3497	1837	1889		
		2 (2.000)	2221	3498	1838	1899		
8-32	.375 (3/8)	3/8 (.375)	1926A	2315A	1452A	1549A		
		1/2 (.500)	1926B	2315B	1452B	1549B		
		5/8 (.625)	1926C	2315C	1452C	1549C		
		3/4 (.750)	1926D	2315D	1452D	1549D		
		1 (1.000)	1926E	2315E	1452E	1549E		

NOTE: Spacers over 1.000 long are tapped .375 deep each end.