



PART NO.	DIM. "A"	DIM. "B"	DIM. "C"	THREAD "S"/"I"	DIM. "F"	
NTS-7	.28 (7.0)	.24 (6.0)	.25 (6.3)	M3/M3	.24 (6.0)	
NTS-8	.31 (8.0)		.24 (6.0)		.31 (8.0)	
NTS-10	.39 (10.0)		.24 (6.1)		.39 (10.0)	
NTS-11	.43 (11.0)		.25 (6.4)			
NTS-12	.50 (12.7)		.24 (6.1)			
NTS-16	.63 (16.0)		.24 (6.0)			
NTS-17.5	.69 (17.5)		.24 (6.1)		M4/M4	.31 (8.0)
NTS-20	.79 (20.0)		.26 (6.5)			
NTS-25	.98 (25.0)		.24 (6.0)			
NTS-15A	.59 (15.0)		.22 (5.5)			
NTS-19	.75 (19.1)					
NTS-37	1.46 (37.1)					

NOTES:

- MATERIAL: NYLON 6/6 (RMS-74).
FLAME RETARDANT NYLON (RMS-146),
AVAILABLE BY SPECIAL ORDER.
TO ORDER ADD "-146" AS SUFFIX.
- COLOR: NATURAL.

TITLE: NYLON THREADED SPACERS			DWG IN IN (MM)		FINAL			
E	SEE CO 200604 FOR CHANGES	SK 12.01.10	TOLERANCES UNLESS NOTED	FILE # NTS	DWN: P.B.	APP:	PART #	
D	SEE CO 200041 FOR CHANGES	SK 09.28.07	.XX=±.010	MAT'L: SEE NOTES	DT: 07-24-95	DT:	PRINT TYPE	
C	SEE ECN #522 FOR CHANGES	SM 11.14.02	.XXX=±.005	RE: RICHCO, INC.	RICHCO INC.		SEE TABLE	
B	CHANGED FILE NO.	SM 06.07.02	FRAC=±1/64		PO BOX 804238, CHICAGO, 60680		CA	
A	REMOVED RMS-01	SM 02.09.01	ANG=±1°		(773) 539-4060			
REV	DESCRIPTION	ENGR DATE						