




TO SNAP-LOCK IN A .187±.003
[4.75±0.08] DIA. HOLE, IN A
.031-.078 [0.79-1.98] PANEL THICKNESS

- NOTES:
1. MATERIAL: "IMPACT MODIFIED" NYLON 6/6 (RMS-73)
AVAILABLE BY SPECIAL ORDER ONLY.
TO ORDER RELACE "-01" WITH "-73".
MATERIAL: " HEAT RESISTANT" NYLON 4/6 UL 94 V-2 (RMS-109)
AVAILABLE BY SPECIAL ORDER ONLY.
TO ORDER REPLACE "-01" WITH "-109"
 2. COLOR: BLACK AVAILABLE BY SPECIAL ORDER ONLY.
TO ORDER ADD SUFFIX "BK" TO PART NO.
 3. PART IS ALSO AVAILABLE IN A 1/8 (3.2) THICK CHASSIS BY
SPECIAL ORDER ONLY. TO ORDER USE P/N: PS-2-XX-XX

| MATERIAL: NYLON 6/6 UL 94 V-2 (RMS-01) COLOR: NATURAL PART NO. | MATERIAL: NYLON 6/6 UL 94 V-0 (RMS-19) COLOR: NATURAL PART NO. | DIM. "A" ±.015 [0.4] |
|---|---|-------------------------|
| PS-3-01 | PS-3-19 | 3/16 [4.8] |
| PS-4-01 | PS-4-19 | 1/4 [6.4] |
| PS-6-01 | PS-6-19 | 3/8 [9.5] |
| PS-7-01 | PS-7-19 | 7/16 [11.1] |
| PS-8-01 | PS-8-19 | 1/2 [12.7] |
| PS-10-01 | PS-10-19 | 5/8 [15.9] |
| PS-12-01 | PS-12-19 | 3/4 [19.1] |
| PS-14-01 | PS-14-19 | 7/8 [22.2] |



TYPICAL APPLICATION

| | | | | | | | | | | | |
|--|-----------------------------------|-------|----------|---|------------------|--|--------------|--|--------|------------|----|
| SPECIAL ORDER ONLY: TO ORDER USE P/N: PS-2-XX-XX | | | | TITLE: PUSH SPACER | | | |  DWG IN IN [MM]  | | | |
| | | | | CREATED USING SOLIDWORKS | FILE #: PS | | DWN: SK | APP: SK | FINAL | | |
| H | SEE ECN #1208 FOR CHANGES | SK | 11/29/06 | TOLERANCES UNLESS NOTED XX±.010 XXX±.005 FRAC. ±1/64 ANG. ±1° | SHEET: 1 OF 1 | SHEET SIZE: A | DT: 02/24/05 | CHKD: DZ | PART # | PRINT TYPE | |
| G | SEE ECN #1196 FOR CHANGES | SK | 07/17/06 | | RE: RICHCO, INC. | RICHCO, INC. ENG@RICHCO-INC.COM (773) 539-4060 | | | | SEE TABLE | CA |
| F | COMPLETELY REDRAWN, SEE ECN #949 | SK | 02/24/05 | | | | | | | | |
| - | SEE ENGINEERING FOR REVISIONS A-E | - | - | | | | | | | | |
| REV. | DESCRIPTION | ENGR. | DATE | | | | | | | | |