



PART NO.	"A"
SRSCBS-6-01	3/8 (9.5)
SRSCBS-7-01	7/16 (11.1)
SRSCBS-8-01	1/2 (12.7)
SRSCBS-10-01	5/8 (15.9)
SRSCBS-12-01	3/4 (19.1)
SRSCBS-14-01	7/8 (22.2)
SRSCBS-16-01	1 (25.4)

USE RICHCO RIVET NO.	FOR CHASSIS THICKNESS
SR-4050	.026-.062 (0.7-1.6)
SR-4060	.062-.105 (1.5-2.7)
SR-4070	.105-.145 (2.7-3.7)
SR-4080	.145-.184 (3.7-4.7)
SR-4090	.184-.223 (4.7-5.7)
SR-4100	.223-.263 (5.7-6.7)
SR-4120	.282-.341 (7.2-8.7)

NOTES:

1. MATERIAL: NYLON 6/6 (RMS-01).
FLAME RETARDANT, NYLON (RMS-19),
AVAILABLE BY SPECIAL ORDER ONLY.
2. COLOR: NATURAL.
3. M3 & M4 THREAD AVAILABLE BY SPECIAL ORDER ONLY.
TO ORDER, ADD "-M3" OR "-M4" TO PART NO.
EXAMPLE: SRSCBS-M3-8-XX
SRSCBS-M4-8-XX
4. .157 TO .161 (4.0 TO 4.1) DIA. HOLE
IN CHASSIS REQUIRED FOR APPLICATION

TOLERANCES UNLESS NOTED		FILE #	DWN:	APP:	DWG IN IN (MM)	FINAL	PRINT TYPE
.XX=±.010 .XXX=±.005 FRAC=±1/64 ANG=±1°		SRSCBS	P.B.				
D	SEE CO 200401 FOR CHANGES	SK 07.30.09					CA
C	SEE ECN #1253 FOR CHANGES	SK 11.29.06					
B	SEE ECN #1002 FOR CHANGES	SK 05.11.05					
A	UPDATED PRINT AND CHANGED FILE NO.	SM 05.09.02					
REV	DESCRIPTION	ENGR	DATE				
TITLE: SNAP RIVET STUDDED CIRCUIT BOARD SUPPORT		MAT'L: SEE NOTES	DT: 05-03-94	DT:	PART #	SEE TABLE	
		RE: RICHCO, INC.	RICHCO INC. PO BOX 804238, CHICAGO, 60680 (773) 539-4060				