



SECTION A-A

NOTES:

1. MATERIAL: PVC, SOFT (RMS-55).
COLOR: BLUE, TRANSLUCENT.
2. FOR "SPASH PROOF SEAL"
RECOMMENDED WIRE OD=.088 TO .120
(2.2 TO 3.1).

TITLE: INSULATING SLEEVE FOR PIN PLUG			DWG IN IN (MM)		FINAL		PRINT TYPE	
E	FILE NO. WAS ISFPP	SM 10.30.02	TOLERANCES UNLESS NOTED	FILE # 224210	DWN: P.B.	APP:	PART #	
D	RMS-55 WAS RMS-126	RG 09.26.01	.XX=±.010	MAT'L: SEE NOTES	DT: 03-23-95	DT:	224210	
C	ADDED RMS-126 TO MATERIAL NOTE; CHANGED FILE NO. AND TITLE BLOCK	SM 06.26.01	.XXX=±.005	RE: RICHCO, INC.	RICHCO INC. PO BOX 804238, CHICAGO, 60680 (773) 539-4060		PRINT TYPE	
B	CONV. TO ACAD; COLOR CHANGE-SEE ECN 128	PB 03.23.95	FRAC=±1/64					CA
A	INSIDE DIA. .085 WAS .090	JP 09.12.90	ANG=±1°					
REV	DESCRIPTION	ENGR DATE						