

[Home](#) > [Products](#) > [Clock / Timing Devices](#) > [PC-Notebook-Server Clocks](#) > [Clock Synthesizer by Chipset Vendor](#) > [Desktop Chipsets](#) > [954135](#) > [954135AFLFT](#)

[Add to myIDT \[?\]](#)

You may also like...

954135AFLFT

Category: [Desktop Chipsets](#)

Generic Part: [954135](#)

Market Group: [PC CLOCK](#)

Description: [PC MAIN CLOCK](#)

ICS954135 provides Intel CK410 compliant clocking. This clock synthesizer provides a single chip solution for next generation Intel chipsets. ICS954135 is driven with a 14.318MHz crystal. It generates CPU outputs up to 400MHz, while providing highly accurate Serial ATA and PCI-Express clocks.

Output Features:

- 2 - 0.7V current-mode differential CPU pairs
- 4 - 0.7V current-mode differential SRC pairs for SATA and PCI-Express
- 1 - 0.7V current-mode differential CPU_I/TP/SRC selectable pair
- 4 - PCI Clocks (33 MHz)
- 2 - PCI Free Running Clocks (33 MHz)
- 2 - USB Clocks (48 MHz)
- 1 - 0.7V current-mode differential DOT clock pair (96 MHz)
- 2 - 14.31818 MHz Reference Clocks



Parameters

Package	SSOP 48 (PVG48)
Voltage	3.3 V
Package	SSOP 48
Speed	NA
Temperature	C
Status	Active
Sample	No
Minimum Order Quantity	1000
Factory Order Increment	1000

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

Type	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

Package

Description	SSOP 300 MIL, 48LD
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Green
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temperature	260°C
Rebake Conditions	NA
Length	15.9
Mark	PVG
Width	7.5
Pitch	0.64
Thickness	2.3
Status	Active