

952926CGLFT

Category: Desktop Chipsets

Generic Part: 952926

Market Group: PC CLOCK

Description: ICS
ICS952926 is a 48 pin clock chip for VIA VX/CX700 style chipsets. When used with a fanout DDR buffer, such as the 93788, it provides all the necessary clock signals for such a system.

Output Features: 3 - 0.7V current-mode differential CPU pairs

- 10 - PCI, 3 free running, 33MHz
- 2 - REF, 14.318MHz
- 3 - 3V66, 66.66MHz
- 1 - 48MHz
- 1 - 24/48MHz
- 2 - 25MHz, 2 free running @2.5V or 3.3V

Time is money

Parameters

Temperature	C
Voltage	3.3 V
Package	TSSOP 48
Speed	NA
Status	Active
Sample	Yes
Minimum Order Quantity	1000
Factory Order Increment	1000

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

Type	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

Package

Package	TSSOP 48 (PAG48)
Description	TSSOP 6.1 MM 0.5MM PITCH
Status	Active
Class	PLASTIC
Category	Green
Pb (Lead) Free	Yes
Mark	G
Package Type	TSSOP
Lead Count	48
Length	12.5 mm
Width	6.1 mm
Thickness	1.0 mm
Pitch	0.5 mm
Tube / Tray	TUBE
Quantity per Tube/Tray	38
Quantity per Reel	1000
Moisture Sensitivity Level (MSL)	1
Moisture Exposure Floor Life	Unlimited@<30C/85%RH
Peak Reflow Temperature	260Â°C
Rebake Conditions	NA
Related Package Documents	view documents