

[Home](#) > [Products](#) > [Clock / Timing Devices](#) > [PC-Notebook-Server Clocks](#) > [Clock Synthesizer by Chipset Vendor](#) > [Desktop Chipsets](#) > [952909](#) > [952909AKLF](#)

[Add to myIDT \[?\]](#)

You may also like...

952909AKLF


Category: Desktop Chipsets

Generic Part: 952909

Market Group: PC CLOCK

Description: PC MAIN CLOCK

ICS952909 is a 56 pin clock chip for VIA PT880/PM880 style chipsets. When used with a fanout DDR buffer, such as the 93788, it provides all the necessary clock signals for such a system. Output Features: ϕ 3 - 0.7V current-mode differential CPU pairs ϕ 10 - PCI, 3 free running, 33MHz ϕ 2 - REF, 14.318MHz ϕ 3 - 3V66, 66.66MHz ϕ 1 - 48MHz ϕ 1 - 24/48MHz ϕ 2 - 25MHz @ 2.5V



Parameters

Package	VFQFPN 56 (NLG56)
Voltage	3.3 V
Package	VFQFPN 56
Speed	NA
Temperature	C
Status	Active
Sample	Yes
Minimum Order Quantity	260
Factory Order Increment	260

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

Type	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

Package

Description	VFQFP-N 8.0 X 8.0 X 0.9 MM - NO LEAD
Class	PLASTIC
Moisture Sensitivity Level (MSL)	3
Category	Green
Moisture Exposure Floor Life	168 hrs. @ <30°C/60%RH
Peak Reflow Temperature	260°C
Rebake Conditions	48 hrs.@125°C
Length	8.0
Mark	K
Width	8.0
Pitch	0.5
Thickness	0.85
Status	Active