932S890BKLFT

Category:	Miscellaneous
Generic Part:	932S890B
Description:	PC MAIN CLOCK

You may also like...

Parameters

Package	VFQFPN 72
Speed	NA
Temperature	C
Voltage	1.8 V

Sales and Support

Sales Offices

- Sales Offices and authorized distributors

Technical Support

Clock Help

- WWW: Clock Help
- Email: mailto:pcclockhelp@idt.com?subject=Technical%20Support%20-%20PC%20Clocks%3A%20&body=%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%0D%0AName%3A%20%20%0D%0ACompany%3A%20%20%20%0D%0ACity/State%3A%20%20%20%0D%0ACountry%3A%0D%0A%0D%0AProduct%20and/or%20Part%20Number%28s%29%3A%0D%0A%0D%0A%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%3D%0D%0A%0D%0A

Package

Package	VFQFPN 72 (NLG72)
Description	VFQFP-N 10.0 X 10.0 X 0.9 MM - NO LEAD
Status	Active
Class	PLASTIC
Category	Green
Pb (Lead) Free	Yes
Pb Free Category	e3 Sn
Mark	K
Package Type	VFQFPN
Lead Count	72
Length	10.0 mm
Width	10.0 mm
Thickness	1.0 mm
Pitch	0.5 mm
Tube / Tray	TRAY
Quantity per Tube/Tray	168
Quantity per Reel	1000
Moisture Sensitivity Level (MSL)	3
Moisture Exposure Floor Life	168hrs@<30C/60%RH
Peak Reflow Temperature	260°C
Rebake Conditions	48hrs@125C
Related Package Documents	view documents

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

Type	Title	Size	Revision Date
Product Change Notice	PCN# : A0808-02 ALTERNATE ASSEMBLY LOCATION FOR VFQFP-N-64 AND VFQFP-N-72	129 KB	08/27/2008

Use of this website signifies your agreement to the acceptable use and privacy policy. Copyright © 1997-2009 Integrated Device Technology, Inc. All Rights Reserved.

Downloaded from Elcodis.com electronic components distributor