

MODEL TL-5101



International size reference: 1/2AA, ER14252

TECHNICAL DATA

(Typical values @+25°C for batteries stored for one year or less)



| | |
|--|-----------------|
| ■ Nominal capacity @ 0.5 mA, to 2V | 0.95 Ah |
| ■ Rated voltage | 3.6 V |
| ■ Weight | 9.2g (0.324 oz) |
| ■ Volume | 4.3 cc |
| ■ Operating temperature range | -55°C to +85°C |
| ■ U.L. Component Recognition, MH 12193 | |

TADIRAN
LITHIUM
BATTERIES



AVAILABLE TERMINATIONS

| | |
|----------------------------|---------------|
| SUFFIX- /S STANDARD | 15-5101-21000 |
| SUFFIX- /T SOLDER TABS | 15-5101-31000 |
| SUFFIX- /P AXIAL PINS | 15-5101-41000 |
| SUFFIX- /PT2 RADIAL PINS | 15-5101-36000 |
| SUFFIX- /TP POLARIZED TABS | 15-5101-52000 |
| SUFFIX- /PT POLARIZED TABS | 15-5101-53000 |



MEMORY BACKUP

Note: Any presentations in this data sheet concerning performance are for information purpose only and are not construed as warranties either expressed or implied, of future performance. Rev. B 03/03