

MODEL TLH-5955



International size reference: 2/3AA, ER14335

TECHNICAL DATA

(Typical values @ +25°C for batteries stored for one year or less)



- Nominal capacity @ 1.3 mA, to 2 V 1.40 Ah
- Rated voltage 3.6 V
- Maximum recommended continuous current 75 mA
- Maximum pulse current capability 150 mA
- Weight 12.5 g (0.441 oz)
- Volume 5.2 cc
- Operating temperature range -55 °C to +125 °C
- Li metal content approx. 0.5 g
- U.L. Component Recognition, MH 12193

TADIRAN
LITHIUM
BATTERIES



TERMINATIONS & ORDERING NO.

SUFFIX- /S STANDARD	15-5955-21505
SUFFIX- /T SOLDER TABS	15-5955-31505
SUFFIX- /P AXIAL PINS	15-5955-41505
SUFFIX- /PT2 RADIAL PINS	15-5955-36505
SUFFIX- /TP POLARIZED TABS	15-5955-52505
SUFFIX- /PT POLARIZED TABS	15-5955-53505



Extended Temperature Range

Note: Any presentations in this data sheet concerning performance are for information purpose only and are not construed as warranties either expressed or implied, of future performance.

ECN 1501187 Rev. A 01/06