


3M™ Twisted Pair Flat Cable

.050" 28 AWG Stranded, Mass Terminable, Halogen Free Polyolefin

2100 Series



- Advantage of this halogen free insulation are low smoke (BSS 7238) and low toxicity of combustion gases (NES 713) reducing the risk to firefighters and low corrosivity of combustion gases (pH≈6.0) reducing damage to nearby equipment
- 28 AWG stranded conductors on .050 inch pitch permits mass terminations to a broad line of IDC connectors
- Please contact your 3M sales representative for variations not described in this specification
- See Regulatory Information Appendix (RIA) for chemical compliance information (RIA E1 & C1 apply)

Date Modified: Septmeber 9, 2010

TS-0762-D
Sheet 1 of 2

Physical

Insulation:

Material: Halogen-Free Polyolefin (PO) Appendix C1 & E1 apply.

Color: Blue / Off-White Pairs

Marking:

Standard: None

Conductors: 28 AWG 7 × 36 [0.127] Tinned Stranded Copper

Electrical

Voltage Rating: USA: 150V EU: <50V

Insulation Resistance: $>10^{10} \Omega/10 \text{ ft. [3 m]}$

Characteristic Impedance: Unbalanced 102 Ω Balanced 119 Ω

Capacitance: 16.9 pF/ft [55.4 pF/m] 14.6 pF/ft [47.9 pF/m]

Inductance: 0.18 $\mu\text{H}/\text{ft}$ [0.59 $\mu\text{H}/\text{m}$] 0.21 $\mu\text{H}/\text{ft}$ [0.69 $\mu\text{H}/\text{m}$]

Propagation Delay: 1.74 ns/ft [5.71 ns/m] 1.73 ns/ft [5.68 ns/m]

Velocity of Propagation: 58% 59%

Note: Unbalanced is measured between ground-signal-ground conductors. Balanced is measured between conductors within a pair.

Environmental

Temperature Rating: -20°C to +80°C

Flammability Rating: USA: UL VW-1 EU: IEC 332-1 & -3

UL File No.: E42769, Style No: 21008

3M
Interconnect Solutions
<http://www.3M.com/interconnects/>


3M is a trademark of 3M Company.
For technical, sales or ordering information call
800-225-5373

3M™ Twisted Pair Flat Cable

.050" 28 AWG Stranded, Mass Terminable, Halogen Free Polyolefin

2100 Series

Number of Conductors	3M Part Number	Dimension A	Dimension B
10 (5 pair)	2100/10TP	0.50 [12.7]	0.450 ± .010 [11.43]
14 (7 pair)	2100/14TP	0.70 [17.8]	0.650 ± .010 [16.51]
16 (8 pair)	2100/16TP	0.80 [20.3]	0.750 ± .010 [19.05]
20 (10 pair)	2100/20TP	1.00 [25.4]	0.950 ± .010 [24.13]
24 (12 pair)	2100/24TP	1.20 [30.5]	1.150 ± .010 [29.21]
26 (13 pair)	2100/26TP	1.30 [33.0]	1.250 ± .010 [31.76]
34 (17 pair)	2100/34TP	1.70 [43.2]	1.650 ± .015 [41.91]
40 (20 pair)	2100/40TP	2.00 [50.8]	1.950 ± .015 [49.53]
50 (25 pair)	2100/50TP	2.50 [63.5]	2.450 ± .015 [62.23]
60 (30 pair)	2100/60TP	3.00 [76.2]	2.950 ± .015 [74.93]
64 (32 pair)	2100/64TP	3.20 [81.3]	3.150 ± .015 [80.01]



- Note:
- Blue edge conductor designates White of pair one.
 - Dimension B pertains to bond to area only.

	Inch [mm]		
	Tolerance Unless Noted		
	.0	.00	.000
Inch	±.1	±.01	±.005

[] Dimensions for Reference Only

Ordering Information

2100/XX TP XX

Number of Conductors (See Table) Blank = Standard
SF = Splice Free

- Note:
- Available in standard lengths of 30 m and 100 m per roll, please specify when ordering.
 - Standard product has a 50 mm flat on 500 mm repeat (2" bond on 19.7" repeat). For special requirements, please contact your 3M sales representative. The flat can be specified anything over 25 mm (1"), the repeat can be specified from 16.5 cm to 1.2 m (6.5" to 48").

TS-0762-D
Sheet 2 of 2

3M
Interconnect Solutions
<http://www.3M.com/interconnects/>

3M is a trademark of 3M Company.
For technical, sales or ordering information call
800-225-5373

DISCONTINUED - See TS-2344 for the New HF100 Series

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**



3M Electronics Solutions Division
6801 River Place Blvd.
Austin, TX 78726-9000
U.S.A.
1-800-225-5373
www.3Mconnector.com

Please recycle. Printed in USA.
© 3M 2010. All rights reserved.
RIA-2217B-E

3M is a trademark of 3M Company.