

Home > Products > Clock / Timing Devices > PC-Notebook-Server Clocks > Single-ended I/O Fan-out and Zero Delay Buffers > 9112-22 > 9112M-22

[Add to myIDT \[?\]](#)

You may also like...

## 9112M-22

**Category:** Single-ended I/O Fan-out and Zero Delay Buffers

**Generic Part:** 9112-22

**Market Group:** PC CLOCK

**Description:** PC BUFFER  
 The ICS9112-22 is a high performance, low skew, low jitter clock driver. It is designed to distribute high speed clocks in PC systems operating at speeds from 25 to 133 MHz.



### Parameters

Package	SOIC 8 (DC8)
Voltage	3.3 V
Package	SOIC 8
Speed	NA
Temperature	C
Status	Active
Sample	Yes
Minimum Order Quantity	194
Factory Order Increment	97

### Distributor Inventory

No Pricing information is available from our Distributors at this time.

### Documents

Type	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

### Package

Description	SOIC(SOP) 150 ML, 8 LD
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Standard
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temperature	240°C
Rebake Conditions	NA
Length	4.9
Mark	S
Width	3.9
Pitch	1.27
Thickness	1.5
Status	Active