

**ebm-papst St. Georgen GmbH & Co. KG**

Hermann-Papst-Straße 1

78112 St. Georgen

Phone: +49 7724 81-0

Fax: +49 7724 81-1309

www.ebmpapst.com

info2@de.ebmpapst.com

Nominal data

Type	8800 TA	
Nominal voltage	[VAC]	115
Speed	[min ⁻¹]	2450
Power input	[W]	11.0
Min. ambient temperature	[°C]	-10
Max. ambient temperature	[°C]	70
Air flow	[m ³ /h]	34
Sound pressure level	[dB(A)]	23

ml = max. load · me = max. efficiency · rfa = running at free air · cs = customer specs · cu = customer unit
Subject to alterations

Technical features

Dimensions	76 Ø x 37 mm
General description	AC fan with external rotor shaded-pole motor
Connection line	2 single strands AWG 28, TR 64
Direction of protection	Right, looking at rotor
Direction of air flow	Inlet via mounting bracket.
Note	Flow rates and noise levels of fans without external housing depend on installation circumstances. The air flow stated here was determined with an orifice of 76.5 mm Ø and at a distance of approximately 17 mm from the mounting bracket. Under exceptionally favorable mounting conditions, the air flow of fan series 8000 A is achievable. The noise in the optimal operating range can only be measured for these fans in a specific application.
Bearing	Sintec sleeve bearing system
Lifetime L10 at 40 °C	55000 h
Lifetime L10 at maximum temperature	27500 h
Mass	0.370 kg
Material of impeller	Metal
Motor protection	Protected from overload using impedance protection
Option	Flow rates and noise levels of fans without external housing depend on installation circumstances. The air flow stated here was determined with an orifice of 76.5 mm Ø and at a distance of approximately 17 mm from the mounting bracket. Under exceptionally favorable mounting conditions, the air flow of fan series 8000 A is achievable. The noise in the optimal operating range can only be measured for these fans in a specific application.
Approval	VDE, CSA, UL, CE

Product drawing

